

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy. of T. 19 S., R. 8 W.

CHAINS

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 19 S  
 $\frac{1}{4}$  S 18  
 R 8 W  
 1957

from which

A fir, 41 ins. diam., bears N.  $77\frac{1}{2}^{\circ}$  E., 41 lks. dist., mkd.  $\frac{1}{4}$  S 18 BT.

A fir, 30 ins. diam., bears S.  $66^{\circ}$  E., 19 lks. dist., mkd.  $\frac{1}{4}$  D 18 BT.

Ascend 180 ft. over SE. slope.

47.55 Small spur, slopes E.; desc. 10 ft. over NE. slope.

49.20 Ravine, course S.  $80^{\circ}$  E.; asc. 275 ft. over SE. slope.

61.635 Point for the N  $\frac{1}{16}$  sec. cor. of sec. 18 only.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

N  $\frac{1}{16}$   
 S 18  
 1957

from which

A fir, 26 ins. diam., bears N.  $16\frac{3}{4}^{\circ}$  E.,  $56\frac{1}{2}$  lks. dist., mkd. N  $\frac{1}{16}$  S 18 BT.

A fir, 27 ins. diam., bears S.  $15\frac{1}{4}^{\circ}$  E., 142 lks. dist., mkd. N  $\frac{1}{16}$  S 18 BT.

Ascend 300 ft. over SE. slope.

68.95 Jeep road, from Roman Nose Mountain to Leopold Creek, bears N.  $60^{\circ}$  W. and S.  $60^{\circ}$  E.

69.60 Same road, bears N.  $70^{\circ}$  E. and S.  $70^{\circ}$  W.

71.00 Same road, bears N.  $75^{\circ}$  W. and S.  $75^{\circ}$  E.

71.25 Spur, slopes SE.; ascend 190 ft. over general SE. slope.

79.94 Point for the  $\frac{1}{4}$  Sec. Cor. of Sec. 13 only, on the E. bdy of T. 19 S., R. 9 W., at midpoint between closing corners.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 19 S  
 $\frac{1}{4}$  S 13  
 R 9 W  
 1957

from which

A fir, 32 ins. diam., bears N.  $56\frac{1}{2}^{\circ}$  W., 126 lks. dist., mkd.  $\frac{1}{4}$  S 13 BT.

A fir, 30 ins. diam., bears S.  $87^{\circ}$  W., 127 lks. dist., mkd.  $\frac{1}{4}$  S 13 BT.

Ascend 50 ft. over SE. slope.