

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy. of T. 19 S., R. 8 W.

CHAINS

From this point a fir, 40 ins. diam., bears N. 75° W., 14 lks. dist. with healed blazes on N., S., and E. sides, more recent than the Collier or Chandler surveys.

Ascend 3 ft. over SW. slope.

41.79 The  $\frac{1}{4}$  sec. cor. of sec. 7 only, determined at record bearing and distance from each of the original bearing trees:

A fir, 53 ins. diam., bears N. 40° W., 60 lks. dist., plainly blazed and healed.

A fir, 27 ins. diam., bears S. 33° E., 24 lks. dist., plainly blazed and healed.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 19 S  
 $\frac{1}{4}$  S 7  
R 8 W  
1957

from which a new bearing tree:

A hemlock, 12 ins. diam., bears N. 1 $\frac{1}{2}$ ° E., 44 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

N. 0° 15' E., beginning new measurement.

Ascend 75 ft. over SW. slope, through heavy timber and dense undergrowth.

8.20 Spur, slopes N. 80° W.; desc. 125 ft. over NW. slope.

13.90 Branch, 2 lks. wide, course N. 70° W.; asc. 125 ft. over SW. slope.

21.65 Top of ascent, slopes W.; desc. 275 ft. over N. slope, changing to NE. slope.

38.68 Point for the  $\frac{1}{4}$  sec. cor. of sec. 12 only, on the E. bdy. of T 19 S. R. 9 W., at midpoint between closing corners.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 19 S  
 $\frac{1}{4}$  S12  
R 9 W  
1957

from which

A hemlock, 22 ins. diam., bears N. 39 $\frac{1}{2}$ ° W., 36 lks. dist., mkd.  $\frac{1}{4}$  S12 BT.

A fir, 10 ins. diam., bears S. 44° W., 88 lks. dist., mkd.  $\frac{1}{4}$  S12 BT.

Descend 40 ft. over NE. slope.

41.48 The cor. of secs. 6 and 7 only, determined at record distance from each of the original bearing trees:

A fir, 52 ins. diam., bears N. 40° E., 32 lks. dist., plainly blazed & healed. (Record bearing, N. 16 $\frac{1}{2}$ ° E.)