

County Surveyor's Record, Douglas County, Oregon

-12-

Dependent Resurvey of a Portion of the W. Bdy of T. 19 S., R. 8 W.

CHAINS

A fir, 55 ins. diam., bears S. 46° E., 50 lks. dist.,
plainly blazed and healed (Record bearing, S. 43½° E.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,
with brass cap mkd.

T 19 S	T 19 S
S 12	S 6 S 7
R 9 W	R 8 W
1957	

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, alder, maple, and scattering yew;
undergrowth, vine maple, salmonberry, evergreen huckleberry, red
huckleberry, hazel, and arrowwood.

N. 0° 13' E., along the W. bdy. of sec. 6.

Descend 12 ft. over NE. slope, through heavy timber and dense
undergrowth.

- 0.75 New line tree, a fir, 45 ins. diam., with 2 hack marks each on
N. and S. side.
- Descend 150 ft. over NE. slope.
- 6.10 Creek, 10 lks. wide, course N. 75° W.; asc. 70 ft. over SW. slope.
- 13.20 Top of ascent, slopes W.; desc. 200 ft. over N. slope.
- 22.20 Branch, 3 lks. wide, course S. 80° W.; asc. 40 ft. over SW. slope.
- 24.80 Top of ascent, slopes W.; desc. 80 ft. over NW. slope.
- 30.10 Ravine, course N. 75° W.; asc. 20 ft. over SW. slope.
- 35.20 Top of ascent, slopes W.; desc. 115 ft. over NW. slope.
- 38.535 Point for the closing cor. of secs. 1 and 12, T. 19 S., R. 9 W.,
at proportionate distance; there is no remaining evidence of the
original corner.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,
with brass cap mkd.
- | | |
|---------|------------|
| T 19 S | T 19 S |
| CC S 12 | S 1
S 6 |
| R 9 W | R 8 S |
| 1957 | |
- from which
- A fir, 23 ins. diam., bears N. 76° W., 12 lks. dist.,
mkd. T19S R9W S1 CC BT.
- A fir, 10 ins. diam., bears S. 50° W., 31 lks. dist.,
mkd. T19S R9W S12 CC BT.
- Descend 50 ft. over NW. slope.
- 40.40 Ravine, course W.; asc. 15 ft. over SW. slope.
- 41.29 The ¼ sec. cor. of sec. 6 only, determined at record distance
from each of the original bearing trees: