

County Surveyor's Record, Douglas County, Oregon

-14-

Dependent Resurvey of a Portion of the W. Bdy. of T. 19 S., R. 8 W.

CHAINS

55.375

The closing corner of Tps. 19 S., Rs. 8 and 9 W., remonumented by Norman D. Price in 1927, with an iron post, 3 ins. diam., 8 ins. Above ground, with brass cap mkd.

T 18 S R 8 W
S 31
 S 1/S 6
 R 9 W R 8 W
 CC
 T 19 S
 1927

from which the remaining bearing trees marked by Price:

A fir, 24 ins. diam., bears S. 13° E., 53 lks. dist., with a healed blaze.

The stump hole of an uprooted fir, 24 ins. diam., bears S. 11° W., 62 lks. dist., with scribe marks, BT visible on decayed blaze on fallen trunk.

Remove the iron post set by Price, which is badly rusted.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 18 S R 8 W
S 31
 S 1/S 6
 R 9 W | R 8 W
 CC
 T 19 S
 1957

From which a new bearing tree:

A hemlock 12 ins. diam., bears S. 71 $\frac{3}{4}$ ° W., 42 lks. dist., mkd. T19S R9W S1 CC BT.

Deposit the old iron post at the base of the new iron post as a memorial.

Land, mountainous.

Soil, sandy clay loam, with occasional outcrops of hard rock

Timber, fir, hemlock, cedar, maple, alder, yew and dogwood.

Undergrowth, vine maple, hazel, arrowwood, rhododendron, salmonberry, huckleberry and fern.

Dependent Resurvey of a Portion of the E. Bdy. of T. 19 S., R. 10 W.
 (Restoring the 1899 Survey by Henry L. Chandler)

From the cor. of secs. 25 and 36, only, on the E. Bdy. of T. 19 S., R. 10 W., monumented by a fir, 28 ins. diam., mkd. and witnessed as described in the official record.

N. 4° 24' E., along the E. bdy. of sec. 25, marking and blazing the true line.

Descend 90 ft. over NE. slope, through heavy timber and dense undergrowth.

10.64

Point for the closing corner of secs. 30 and 31, T. 19 S., R. 9 W., at proportionate distance; there is no remaining evidence of the original corner.