

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the E. Bdy. of T. 19 S., R. 10 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 19 S		T 19 S
S 25		S 30
		S 31
R 10 W		R 9 W
		1958

from which

A hemlock, 15 ins. diam., bears N. 24½° E., 57 lks. dist., mkd. T19S R9W S30 CC BT.

A hemlock, 40 ins. diam., bears S. 9° E., 37½ lks. dist., mkd. T19S R9W S31 CC BT.

Descend 40 ft. over NE. slope.

13.20 North Fork of Smith River, 80 lks. wide, course S. 70° E.; asc. 255 ft. over SW. slope.

26.85 Spur, slopes W.; desc. 25 ft. over N.W. slope.

28.20 Branch, 3 lks. wide, course W.; asc. 50 ft. over SW. slope.

35.00 Spur, slopes W.; desc. 260 ft. over NW. slope.

44.00 North Fork of Smith River, 80 lks. wide, course S. 85° W.; asc. 50 ft. over S. slope.

46.48 Point for the ¼ sec. cor. of sec. 25 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 19 S		¼
S 25		
R 10 W		
		1958

from which

A cedar, 13 ins. diam., bears N. 34½° W., 28 lks. dist., mkd. ¼ S25 BT.

A fir, 21 ins. diam., bears S. 11° W., 16 lks. dist., mkd. ¼ S25 BT.

Ascend 179 ft. over S. slope.

50.05 Spur, slopes S. 50° E.; desc. 43 ft. over NE. slope.

57.17 Point for the ¼ sec. cor. of sec. 30 only, on the W. bdy. of T. 19 S., R. 9 W., at midpoint between closing corners.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

		¼
		T 19 S
		S 30
		R 9 W
		1958

from which

An alder, 18 ins. diam., bears N. 7° E., 55 lks. dist., mkd. ¼ S30 BT.