

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the E. Bdy. of T. 19 S., R. 10 W.

CHAINS	
14.70	Spur, slopes NW.; desc. 294 ft. over N. slope.
30.75	Branch, 3 lks. wide, course N. 60° W.; asc. 270 ft. over SW. slope.
41.50	Spur, slopes W.; desc. 200 ft. over NW. slope.
41.50	Branch, 2 lks. wide, course W.; desc. 7 ft. over NW. slope.
45.50	North Fork of Smith River, 70 lks. wide, course SW.; asc. 2 ft. over SE. slope.
46.48	Point for the $\frac{1}{4}$ sec. cor. of sec. 24 only, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground with brass cap mkd.
	$\frac{1}{4}$ T 19 S S 24 R 10 W 1958
	from which
	A hemlock, 25 ins. diam., bears N. 49° W., 96 lks. dist., mkd. $\frac{1}{4}$ S24 BT.
	An alder, 22 ins. diam., bears S. 7 $\frac{1}{2}$ ° W., 105 lks. dist., mkd. $\frac{1}{4}$ S24 BT.
	Ascend 22 ft. over SE slope.
51.00	Top of ascent, slopes E.; desc. 16 ft. over NE. slope.
56.00	North Fork of Smith River, 70 lks. wide, course S. 5° E.; asc. 7 ft. along stream bed.
57.255	Point for the $\frac{1}{4}$ sec. cor. of sec. 19 only, on the W. bdy. of T. 19 S., R. 9 W., at midpoint between closing corners.  St a brass tablet, $3\frac{1}{4}$ ins. diam., $3\frac{1}{2}$ in. stem, $3\frac{1}{2}$ ins. in drill hole, in solid rock, on E. bank of North Fork, which drains from N. 25° W., to S. 5° E., with top mkd.
	$\frac{1}{4}$ T 19 S S 19 R 9 W 1958
	from which
	An alder, 28 ins. diam., bears N. 6° E., 73 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
	An alder, 25 ins. diam., bears S. 54° E., 42 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
	Ascend 210 ft. over SW. slope.
62.60	Spur, slopes W.; desc. 167 ft. over NW. slope.
69.72	Point for the N 1/16 sec. cor. of sec. 24 only.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.