

County Surveyor's Record, Douglas County, Oregon

-20-

Dependent Resurvey of a Portion of the E. Bdy. of T. 19 S., R. 10 W.

CHAINS											
	Ascend 92 ft. over SE. slope.										
63.25	Head of ravine, course S. 70° E.; asc. 516 ft. over S. slope.										
72.65	Spur, slopes N. 30° E.; desc. 87 ft. over NW. slope.										
77.15	Branch, 3 lks. wide, course N. 30° E.; desc. 19 ft. over NE. slope.										
80.20	Ravine, course E.; asc. 149 ft. over S. slope.										
85.30	Spur, slopes E.; desc. 330 ft. over NE. slope.										
92.96	<p>The cor. of secs. 12 & 13 only, monumented with a sandstone, 20x6 x5 ins., firmly set 10 ins. in the ground, with 4 notches on S., and 2 notches on N. edges, from which the original bearing trees:</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears S. 66½° W., 68 lks. dist., plainly blazed & healed. (Record, S. 63° W., 73 lks. dist.)</p> <p style="padding-left: 40px;">An alder stump, 12 ins. diam., bears N. 9° W., 31 lks. dist., with no marks remaining. (Record, N. 5° W., 28 lks. dist.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T 19 S</td></tr> <tr><td>S 12</td><td> S 18</td></tr> <tr><td>S 13</td><td> </td></tr> <tr><td>R 10 W</td><td> R 9 W</td></tr> <tr><td colspan="2">1958</td></tr> </table> </div> <p style="text-align: right; font-style: italic;">Fd. OK 9/19/58 D. BAKER M 107-1</p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 26° W., 46 lks. dist., mkd. T19S R10W S12 BT.</p> <p>Deposit the original stone alongside the base of the iron post.</p> <p>Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, alder, maple, dogwood, and chinquapin. Undergrowth, vine maple, salmonberry, hazel, arrowwood, whododendron, red huckleberry, salal, poison oak, and sword fern.</p>	T 19 S		S 12	S 18	S 13		R 10 W	R 9 W	1958	
T 19 S											
S 12	S 18										
S 13											
R 10 W	R 9 W										
1958											
	N. 0° 59' E., along the E. Bdy. of sec. 12.										
	Descend 200 ft. over NE. slope, through heavy timber and dense undergrowth.										
4.50	Ravine, course N. 20° E.; asc. 150 ft. over SE. slope.										
8.70	Spur, slopes S. 30° E.; desc. 20 ft. over NE. slope.										
8.97	The closing cor. of secs. 7 and 18, T. 19 S., R. 9 W., hereinafter described.										
	Descend 125 ft. over NE. slope.										
10.90	Ravine, course S. 40° E.; asc. 150 ft. over SE. slope.										
16.90	Spur, slopes S. 70° E.; desc. 150 ft. over NE. slope.										
19.80	Ravine, course N. 80° E.; asc. 200 ft. over SE. slope.										
20.40	Spur, slopes E.; desc. 250 ft. over NE. slope.										
38.85	Point for the ¼ sec. cor. of sec. 12 only, at proportionate distance;										

(Pg. 13063)