

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the E. Bdy. of T. 19 S., R. 10 W.

CHAINS

there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

	½
T 19 S	
S 12	
R 10 W	
1958	

*Fd. OK 9/08  
D. BAKER  
M107-1*

from which

A fir, 23 ins. diam., bears N. 27° W., 22 lks. dist., mkd. ¼ S12 BT.

A fir, 15 ins. diam., bears S. 30½° W., 30 lks. dist., mkd. ¼ S12 BT.

Descend 200 ft. over NE. slope.

44.95 Branch, 3 lks. wide, course N. 10° E.; asc. 20 ft. over SE. slope.

48.145 Point for the ¼ sec. cor. of sec. 7 only, on the W. bdy. of T. 19 S., R. 9 W., at midpoint between closing corners.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

	¼
T 19 S	
S 7	
R 9 W	
1958	

from which

A hemlock, 22 ins. diam., bears N. 48½° E., 147 lks. dist., mkd. ½ S7 BT.

A hemlock, 18 ins. diam., bears S. 47° E., 77 lks. dist., mkd. ¼ S7 BT.

Ascend 60 ft. over S. slope.

50.80 Spur, slopes E.; desc. 110 ft. over N. slope.

55.30 Ravine, course S. 80° E.; asc. 380 ft. over S. slope.

65.20 Spur, slopes S. 20° E.; desc. 40 ft. over broken NE. slope.

75.70 Ravine, course E.; asc. 40 ft. over S. slope.

77.70 Point for the cor. of secs. 1 and 12 only, at proportionate distance there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

	T 19 S	
	S 1	
	S 12	S 7
	R 10 W	R 9 W
	1958	

*Fd. OK 9/08  
D. BAKER  
M107-1*

from which

A fir, 27 ins. diam., bears S. 46¼° W., 160 lks. dist., mkd. T19S R10W S12 BT.