

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the E. Bdy. of T. 19 S., R. 10 W.

CHAINS	<p>A fir, 15 ins. diam., bears N. <math>80\frac{1}{2}^\circ</math> W., 42 lks. dist., mkd. T19S R10W S1 BT.</p>
	<p>Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, dogwood, and chinquapin. Undergrowth, vine ample, hazel, arrowwood, salmonberry, elder, red huckleberry, salal, and sword fern.</p>
	<p>N. <math>0^\circ 59'</math> E., along the E. bdy. of sec. 1.</p>
	<p>Ascend 180 ft. over broken S. slope, through heavy timber and dense undergrowth.</p>
9.62	<p>The closing corner of secs. 6 and 7, T. 19 S., R. 9 W., hereinafter described.</p>
11.50	<p>Spur, slopes S. <math>20^\circ</math> E.; desc. 540 ft. over NE. slope, changing to N. slope.</p>
26.20	<p>Ravine, course N. <math>60^\circ</math> E.; asc. 35 ft. over S. slope.</p>
31.30	<p>Ravine, course S. <math>60^\circ</math> E.; asc. 260 ft. over S. slope.</p>
36.50	<p>Road, 20 lks. wide, bears N. <math>60^\circ</math> E. and S. <math>60^\circ</math> W.</p>
38.80	<p>Spur, slopes E.; desc. 3 ft. over N. slope.</p>
38.85	<p>The <math>\frac{1}{4}</math> Sec. cor. of sec. 1 only, determined at record distance from each of the original bearing trees:</p>
	<p>A fir, 32 ins. diam., bears N. <math>42\frac{1}{2}^\circ</math> W., 62 lks. dist., with a heled blaze. (Record bearing, N. <math>44^\circ</math> W.)</p>
	<p>A fir, 30 ins. diam., bears S. <math>60\frac{1}{2}^\circ</math> W., 113 lks. dist., with a healed blaze. (Record bearing, S. <math>59^\circ</math> W.)</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground with brass cap mkd.</p>
	<p style="text-align: center;"> <math>\frac{1}{4}</math>  T 19 S  S 1  R 10 W  1957 </p>
	<p><i>Fl. OK.</i> by: STUNTNER MULKINS &amp; MARCH, 1983 M 94-21 A, B, C</p>
	<p>N. <math>0^\circ 18'</math> E., beginning new measurement.</p>
	<p>Descend 450 ft. over N. slope, changing to NW. slope.</p>
8.91	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 6 only, on the W. bdy. of T. 19 S. R. 9 W., at proportionate distance.</p>
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> <math>\frac{1}{4}</math>  T19 S  S 6  R 9 W  1958 </p>
	<p><i>Fd. OK.</i> by: STUNTNER MULKINS &amp; MARCH, 1983 M 94-21 A, B, C</p>
	<p>from which</p>
	<p>A maple, 20 ins. diam., bears N. <math>77\frac{1}{2}^\circ</math> E., 116 lks. dist., mkd. <math>\frac{1}{4}</math> S6 BT.</p>