

County Surveyor's Record, Douglas County, Oregon

-23-

Dependent Resurvey of a Portion of the E. Bdy. of T. 19 S., R. 10 W.

CHAINS

A A cedar, 11 ins. diam., bears S. $53\frac{1}{2}^{\circ}$ E., 117 lks. dist.,
mkd. $\frac{1}{4}$ S6 BT.

Descend 20 ft. over NW. slope.

9.25 Ravine, course N. 30° E.; asc. 150 ft. over SE. slope.

14.45 Spur, slopes NE.; desc. 170 ft. over NE. slope.

19.35 Branch, 5 lks. wide, course NE.; asc. 50 ft. over S. slope.

27.94 The closing cor. of Tps. 19 S., Rs. 9 and 10 W., monumented with an
iron post, 3 ins. diam., firmly set, mkd. and witnessed as described
in the official record.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, alder, dogwood, cascara, and yew.
Undergrowth, vine maple, hazel, arrowwood, red huckleberry, ever-
green huckleberry, salmonberry, rhododendron, salal, and sword fern.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 19 S., R. 9 W.

(Restoring the 1899 Survey by Henry L. Chandler)

From the cor. of secs. 35 and 36 on the S. bdy. of the Tp.,
monumented with an iron post, 2 ins. diam., firmly set, mkd. and
witnessed as described in the official record.

N. $0^{\circ} 59'$ E., bet. secs. 35 and 36.

Descend 30 ft. over broken NW. slope, through heavy timber and
dense undergrowth, marking and blazing the true line.

2.80 Head of ravine, course N. 35° E.; desc. 45 ft. over broken E. slope.

6.50 Spur, slopes N. 75° E.; desc. 230 ft. over NE. slope.

9.50 Ravine, course S. 85° E., asc. 312 ft. over broken SE. slope,
changing to broken E. slope.

25.35 Spur, slopes S.; desc. 230 ft. over broken N. slope.

31.60 Ravine, course N. 30° E.; desc. 150 ft. over broken NE. slope.

35.20 Spring branch in ravine, course E.; asc. 120 ft. over SE. slope.

40.605 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate
dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground,
with brass cap mkd.

$\frac{1}{4}$
S 35 | S 36
T 19 S R 9 W
1957

from which

A fir, 40 ins. diam., bears N. 86° E., 47 lks. dist.,
mkd. $\frac{1}{4}$ S36 BT.

A fir, 42 ins. diam., bears N. 86° W., 84 lks. dist.,
mkd. $\frac{1}{4}$ S35 BT.

Ascend 150 ft. over broken SE. slope.