

County Surveyor's Record, Douglas County, Oregon

-28-

Dependent Resurvey of Portion of Subdivisional Lines of T. 19 S., R. 9 W.

CHAINS	<p>Descend 103 ft. along broken W. slope.</p>								
68.55	<p>Same logging road, 40 lks. wide, gravelled and maintained, bears N. 10° E. and S. 10° W.</p>								
78.26	<p>Ravine, course W.; asc. 2 ft. over W. slope.</p>								
81.20	<p>Point for the cor. of secs. 11, 12, 13, and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 19 S</td><td>R 9 W</td></tr> <tr><td>S 11</td><td>S 12</td></tr> <tr><td>S 14</td><td>S 13</td></tr> <tr><td colspan="2">1958</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 9° E., 49 lks. dist., mkd. T19S R9W S12 BT.</p> <p style="padding-left: 40px;">A fir, 47 ins. diam., bears S. 57° E., 193 lks. dist., mkd. T19S R9W S13 BT.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears S. 30° W., 12 lks. dist., mkd. T19S R9W S14 BT.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 28° W., 63½ lks. dist., mkd. T19S R9W S11 BT.</p> <p>Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, alder, maple, madrona, cascara, and yew. Undergrowth, vine maple, hazel, arrowwood, red huckleberry, evergreen huckleberry, rhododendron, salal, salmonberry and sword fern.</p>	T 19 S	R 9 W	S 11	S 12	S 14	S 13	1958	
T 19 S	R 9 W								
S 11	S 12								
S 14	S 13								
1958									
	<p>S. 89° 35' E., bet. secs. 12 and 13.</p> <p>Ascend 54 ft. over W. slope, through heavy timber and dense undergrowth.</p>								
0.40	<p>Logging road, 40 lks. wide, gravelled and maintained, bears N. & S.</p>								
3.00	<p>Ridge, divide bet. North Fork of Smith River and Whittaker Creek, bears N. and S.; desc. 100 ft. over broken N. slope.</p>								
13.60	<p>Spur, slopes NE.; desc. 235 ft. over SE. slope, changing to S. slope.</p>								
28.30	<p>Ravine, course SE.; asc. 45 ft. over SW. slope.</p>								
29.30	<p>Spur, slopes S. 20° W.; desc. 30 ft. over SE. slope.</p>								
30.20	<p>Branch, 3 lks. wide, course S. 40° W.; asc. 60 ft. over SW. slope.</p>								
35.60	<p>Spur, slopes SW.; desc. 30 ft. over SE. slope.</p>								
39.39	<p>Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>¼</td><td>S 12</td></tr> <tr><td></td><td>S 13</td></tr> <tr><td colspan="2">T 19 S R 9 W</td></tr> <tr><td colspan="2">1958</td></tr> </table> </div>	¼	S 12		S 13	T 19 S R 9 W		1958	
¼	S 12								
	S 13								
T 19 S R 9 W									
1958									