

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines T. 19 S., R. 9 W.

| | | | | | | | | | | | | | | | | | | | | | | | |
|---------------|--|------|---|-----|---|-----|-----|--|--|------|------|--|--|------|--|--|--|---------------|-----|--|------|------|--|
| CHAINS | <p>from which</p> <p>A fir, 12 ins. diam., bears S. 35° E., 23 lks. dist., mkd. $\frac{1}{4}$ S12 BT.</p> <p>A fir, 23 ins. diam., bears N. 40° W., 28 lks. dist., mkd. $\frac{1}{4}$ S11 BT.</p> <p>Ascend 20 ft. over SW. slope.</p> <p>41.30 Spur, slopes N. 50° E.; desc. 70 ft. over NE. slope.</p> <p>46.70 Ravine, course N. 80° E.; asc. 200 ft. over SE. slope.</p> <p>53.20 Spur, slopes N. 35° E.; desc. 410 ft. over NW. slope.</p> <p>63.80 Ravine, course N. 75° E.; asc. 410 ft. over S. slope.</p> <p>74.40 Spur, slopes N. 75° E.; desc. 300 ft. over NW. slope.</p> <p>81.20 Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 19</td><td>S</td><td>R 9</td><td>W</td></tr> <tr><td>S 2</td><td>S 1</td><td></td><td></td></tr> <tr><td>S 11</td><td>S 12</td><td></td><td></td></tr> <tr><td colspan="4">1957</td></tr> </table> </div> <p>from which</p> <p>A fir, 32 ins. diam., bears N. $6\frac{1}{2}$° E., 33 lks. dist., mkd. T19S R9W S1 BT.</p> <p>A fir, 25 ins. diam., bears S. $72\frac{1}{4}$° E., 34 lks. dist., mkd. T19S R9W S12 BT.</p> <p>A fir, 33 ins. diam., bears S. 44° W., 63 lks. dist., mkd. T19S R9W S11 BT.</p> <p>A fir, 25 ins. diam. bears N. 63° W., 36 lks. dist., mkd. T19S R9W S2 BT.</p> <p>Land, mountainous. Soil, sandy clay loam Timber, fir, hemlock, cedar, alder, maple, cascara, and madrona. Undergrowth, vine maple, arrowwood, hazel, red huckleberry, evergreen huckleberry, salal, and sword fern.</p> <hr/> <p>N. 89° 29' E., bet. secs. 1 and 12.</p> <p>Descend 170 ft. over broken NE. slope, through heavy timber and dense undergrowth.</p> <p>13.40 Ravine, course N. 10° E.; asc. 104 ft. over broken NW. slope.</p> <p>31.40 Top of ascent, slopes N.; desc. 114 ft. along broken N. slope, changing to NE. slope.</p> <p>39.26 Point for the $\frac{1}{4}$ sec. cor. of secs. land 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>$\frac{1}{4}$</td><td>S 1</td></tr> <tr><td></td><td>S 12</td></tr> <tr><td colspan="2">1957</td></tr> </table> </div> | T 19 | S | R 9 | W | S 2 | S 1 | | | S 11 | S 12 | | | 1957 | | | | $\frac{1}{4}$ | S 1 | | S 12 | 1957 | |
| T 19 | S | R 9 | W | | | | | | | | | | | | | | | | | | | | |
| S 2 | S 1 | | | | | | | | | | | | | | | | | | | | | | |
| S 11 | S 12 | | | | | | | | | | | | | | | | | | | | | | |
| 1957 | | | | | | | | | | | | | | | | | | | | | | | |
| $\frac{1}{4}$ | S 1 | | | | | | | | | | | | | | | | | | | | | | |
| | S 12 | | | | | | | | | | | | | | | | | | | | | | |
| 1957 | | | | | | | | | | | | | | | | | | | | | | | |