

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 19 S., R. 9 W.

CHAINS	<p>From the cor. of secs. 34 and 35. on the S. bdy. of the Twp., monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the official record.</p> <p>N. 0° 53' E., bet. secs. 34 and 35.</p> <p>Descend 84 ft. over NW. slope, through heavy timber and dense undergrowth.</p> <p>1.75 Ravine, course N. 40° E.; asc. 142 ft. along E. slope.</p> <p>10.95 Spur, slopes N. 60° E.; desc. 426 ft. over NW. slope.</p> <p>21.35 Branch, 4 lks. wide, course N. 75° E.; asc. 234 ft. over SE. slope.</p> <p>28.60 Spur,, slopes N. 80° E.; desc. 260 ft. over NE. slope.</p> <p>34.55 Branch, 4 lks. wide, course S. 75° E.; asc. 40 ft. over S. slope.</p> <p>36.91 The <math>\frac{1}{4}</math> sec. cor. of secs. 34 and 35, determined at record bearing and distance from each of the original bearing trees:</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears N. 59° E., 24 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 47 ins. diam., bears N. 8° W., 24 lks. dist., with a healed blaze.</p> <p>At the corner point.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="padding-left: 40px;"> <i>Fd. by: I.D. ROBERTS, PLS #1039</i>  <i>4/3/84</i>  <i>SEE C.S. 58/293</i> </p> <p style="padding-left: 100px;"> <math>\frac{1}{4}</math>  S 34   S 35  1957 </p> <p>from which a new bearing tree:</p> <p style="padding-left: 40px;">A cedar, 13 ins. diam., bears N. 6<math>\frac{3}{4}</math>° E., 67 lks. dist., mkd. <math>\frac{1}{4}</math> S35 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 32' E., beginning new measurement.</p> <p>Ascend 405 ft. over general S. slope.</p> <p>10.80 Spur, slopes E.; desc. 442 ft. over general N. slope.</p> <p>23.95 Branch, 10 lks. wide, course E.; asc. 240 ft. over S. slope.</p> <p>28.90 Spur, slopes E.; desc. 240 ft. over NE. slope.</p> <p>37.27 The cor. of secs. 26, 27, 34 and 35, mkd. by the remains of the original corner tree, a decayed alder stump, 18 ins. diam., with no marks remaining, from which the remaining of the original bearing trees:</p> <p style="padding-left: 40px;">An alder, 32 ins. diam., bears S. 10° E., 30 lks. dist., with scribe marks T19S R9W S35 BT. visible on the bark. There marks are greatly expanded. (Record bearing, S.14°E.)</p> <p style="padding-left: 40px;">An alder snag, 20 ins. diam., bears N. 10° W., 17 lks. dist., with no marks remaining.</p> <p style="padding-left: 40px;">There is no evidence of the other bearing trees.</p> <p>At the corner point</p>
--------	---