

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 19 S., R. 9 W.

CHAINS	
34.60	Spur, slopes N.; desc. 20 ft. over W. slope.
39.25	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, mkd. by a dead fir, 15 ins. diam., with no marks remaining on decayed blazes, from which the original bearing trees are as follows:</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 1° E., 11 lks. dist., with blaze healed and burned. I open and uncover fragmentary scribe marks.</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears S. 66° E., 18 lks. dist., plainly blazed and healed.</p> <p>At the corner point, in place of dead fir,</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4} \begin{array}{l} S 3 \\ S 10 \\ 1957 \end{array}$ </div> <p>from which new bearing trees:</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 13° W., 29 lks. dist., mkd. $\frac{1}{4}$ S3 BT.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 53° E., 51 lks. dist., mkd. $\frac{1}{4}$ S10 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 42' W., beginning new measurement.</p> <p>Descend 130 ft. over broken W. slope.</p>
3.10	Ravine, course N. 15° E.; desc. 25 ft. over broken NW. slope.
8.15	Ravine, course N. 25° W.; desc. 50 ft. over broken NW. slope.
18.10	North Fork of Smith River, 15 lks. wide, course N.; asc. gradually over bottom land.
28.95	Edge of bottom land, bears N. and S.; asc. 275 ft. over E. slope, changing to SE. slope.
38.70	Spur, slopes S.; desc. 5 ft. over SW. slope.
39.89	<p>The cor. of secs. 3, 4, 9, and 10, mkd. by a fir snag, 10 ins. diam., plainly blazed and healed, from which the remaining original bearing trees are as follows:</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears N. 25° E., 26 lks. dist., blazed and healed. (Record, N. 43° E., 25 lks. dist.)</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears S. 59$\frac{1}{2}$° E., 18 lks. dist., with scribe marks T19S R9W S10 visible on opened blaze. (Record, S. 52° E., 25 lks. dist.)</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears N. 46$\frac{1}{4}$° W., 15 lks. dist., blazed and healed. (Record, N. 63° W., 8 lks. dist.)</p> <p>At the corner point, in place of fir snag,</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $T 19 S R 9 W$ $\begin{array}{l} S 4 S 3 \\ S 9 S 10 \\ 1957 \end{array}$ </div>

fd. OK July 1981
LES ROBERTS M 88-21