

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 19 S., R. 9 W.

CHAINS

The cor. of secs. 7, 8, 17, and 18, is monumented with a sandstone, 16 x 10 x 6 ins., firmly set, 12 ins. in the ground, with 4 notches on the S., and 5 notches on the E. edges, from which the original bearing trees:

A decayed fir stump, bears N. 22° E., 4 lks. dist.

A fir stump, 18 ins. diam., bears S. 49° E., 48 lks. dist., with scribe marks T19S R9W S17 BT visible on opened blaze. (Record distance, 51 lks.)

A hemlock, 30 ins. diam., bears S. 40° W., 35 lks. dist., with a healed blaze. (Record distance, 33 lks.)

A decayed fir stump, bears N. 75° W., 13 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 19 S R 9 W
S 7 | S 8
S 18 | S 17
1957

from which new bearing trees:

A hemlock, 6 ins. diam., bears N. 83½° E., 41 lks. dist., mkd. T19S R9W S8 BT.

A fir, 25 ins. diam., bears S. 54½° E., 67 lks. dist., mkd. T19S R9W S17 BT.

A fir, 30 ins. diam., bears N. 13° W., 29 lks. dist., mkd. T19S R9W S7 BT.

Deposit the corner stone alongside the iron post.

Thence N. 88° 49' W., bet. secs. 7 and 18.

Descend 30 ft. over NW. slope, through heavy timber and dense undergrowth.

1.50 Branch, 3 lks. wide, course N.; asc. 90 ft. along N. slope.

14.30 Spur, slopes N. 75° W.; desc. 780 ft. over W. slope.

33.20 Trail, bears N. and S.

39.45 Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

FOOD OK
6-21 R. WARD
M113-37 A & B

¼ S 7
S 18
T 19 S R 9 W
1958

FOOD OK 9/28
M107-1
D. BAKER

from which

A fir, 20 ins. diam., bears S. 32° E., 63 lks. dist., mkd. ¼ S18 BT.

A fir, 25 ins. diam., bears N. 42° W., 66 lks. dist., mkd. ¼ S 7 BT.

Descend 20 ft. over W. slope.

Set...
Notes...

103...