

County Surveyor's Record, Douglas County, Oregon

CHAINS

A hemlock stump, 24 ins. diam., bears N. 77° E., 15 lks. dist., with scribe marks $\frac{1}{4}$ S8 visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 7 | S 8
1957

FD. OK 11-91
M 114-27
D. BAKER

FD. OK
9/18/88
M 107-1
D. BAKER

from which a new bearing tree:

A fir, 22 ins. diam., bears S. 59° E., 118 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

No other suitable tree available.

N. 0° 04' E., beginning new measurement.

Descend 30 ft. over N. slope.

- 2.10 Shepherd Creek, 8 lks. wide, course W.; asc. 300 ft. over S. slope.
- 4.20 Dirt road, 25 lks. wide, bears E. and W.
- 18.60 Spur, slopes SW.; desc. 225 ft. over broken NW. slope.
- 36.10 Dirt access road, 25 lks. wide, bears N. 50° E. and S. 50° W.
- 39.05 Point for the cor. of secs. 5, 6, 7, and 8, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 19 S R 9 W
S 6 | S 5
S 7 | S 8
1958

FD. OK 11-91
M 114-27
D. BAKER
FD OK 3/97
D. Baker
M 124-48

FD. OK by:

MULKINS & STUMPFNER
MARCH, 1983
M 94-21 A, B, C

from which

A fir, 12 ins. diam., bears N. 83° E., 253 lks. dist., mkd. T19S R9W S5 BT.

A fir, 16 ins. diam., bears S. 73° E., 211 lks. dist., mkd. T19S R9W S8 BT.

A fir, 20 ins. diam., bears S. 84° W., 347 lks. dist., mkd. T19S R9W S7 BT.

A fir, 12 ins. diam., bears N. 25° W., 102 lks. dist., mkd. T19S R9W S6 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, alder, maple, dogwood, chinquapin, and madrona.

Undergrowth, vine maple, salmonberry, arrowwood, salal, red huckleberry, evergreen huckleberry, hazel, rhododendron, & fern.

From the cor. of secs. 4, 5, 8, and 9.

N. 88° 45' W., bet. secs. 5 and 8.

Descend 30 ft. along top of ridge, through heavy timber and dense undergrowth.