

County Surveyor's Record, Douglas County, Oregon

CHAINS	N.88° 15' W., bet. secs. 6 and 7. Thence over nearly level river bottom land, through light undergrowth.
0.50	Dirt access road, 20 lks. wide, bears N. and S.; continue across bottom land.
3.90	North Fork of Smith River, 40 lks. wide, course S. 10° W.; continue across bottom.
10.80	Leave bottom and enter timber, edge bears N. 70° E. and S. 70° W.; asc. 105 ft. over SE. slope.
11.05	Dirt access road, 25 lks. wide, bears N. 30° E. and S. 30° W.
13.05	Spur, slopes S.; desc. 50 ft. over broken SW. slope.
34.60	Branch, 4 lks. wide, course S. 20° E.; asc. 50 ft. over SE. slope.
38.99	The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, located in the stump hole of an uprooted fir, 10 ins. diam., with fragmentary scribe marks visible on the fallen trunk, from which the original bearing trees: A fir snag, 12 ins. diam., bears N. 24° E., 15 lks. dist., with a healed blaze. A fir stump, 10 ins. diam., bears S. 73 $\frac{1}{2}$ ° E., 15 lks. dist., with fragmentary scribe marks visible on broken blaze. (Record bearing, S. 66° E.) At the corner point. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="display: flex; justify-content: space-between;"> <div style="width: 40%;"> <p>FR. OK by STUNTNER MULKINS MARCH, 1988 M 94 9/88 M107-1 D. BAKER</p> </div> <div style="width: 50%; text-align: center;"> $\frac{1}{4} \frac{S 6}{S 7}$ <p>T 19 S R 9 W 1958</p> </div> </div> <p>from which new bearing trees:</p> <p>A fir, 28 ins. diam., bears N. 22° E., 38 lks. dist., mkd. $\frac{1}{4}$ S6 BT.</p> <p>A hemlock, 13 ins. diam., bears S. 29° E., 86 lks. dist., mkd. $\frac{1}{4}$ S7 BT.</p>
	N. 89° 16' W., beginning new measurement. Ascend 150 ft. over SE. slope.
10.10	Spur, slopes S. 30° E.; desc. 110 ft. over SW. slope.
17.40	Ravine, course SE.; asc. 435 ft. over NE. slope.
34.60	Spur, slopes S. 30° E.; asc. 100 ft. over SE. slope.
39.31	The Chandler closing corner of secs. 6 & 7, monumented with a sandstone, 16 x 12 x 6 ins., mkd. CC on E. face, with 5 notches on the S. and 1 notch on N. edges; from which an original bearing tree: A fir snag, 40 ins. diam., bears N. 56° E., 260 lks. dist., with a healed blaze. There is no evidence of other bearing tree.
39.37	Intersect the E. bdy. of sec. 1, T. 19 S., R. 10 S. Point for the closing corner of sections 6 and 7.

SURVEY
 1/13/88
 1/13/88
 1/13/88