

County Surveyor's Record, Douglas County, Oregon

-2-

Dependent Resurvey of a Portion of the S. Bdy., T. 23 S., R. 7 W.

CHAINS

S. $88^{\circ} 29'$ W., along the S. bdy. of sec. 35, marking and blazing the true line.

Descend 38 ft. over general W. slope, along N. edge of logged area.

6.45 True point for the closing cor. of secs. 1 & 2, T. 24 S., R. 7 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 7 W
 S 35
 S 2 | S 1
 T 24 S R 7 W
 C C
 1962

from which

A white fir, 10 ins. diam., bears S. 50° E., 89 lks. dist., mkd. T24S R7W S1 CC BT.

A white fir, 8 ins. diam., bears S. 27° W., $6\frac{1}{2}$ lks. dist., mkd. T24S R7W S2 CC BT.

From this point the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, T. 24 S., R. 7 W., bears South, 37.48 chs. distant, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, mkd. and witnessed as described in the official record.

From this same point, the original closing corner for secs. 1 and 2, T. 24 S., R. 7 W., bears North, 1.14 chs. distant, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, mkd. and witnessed as described in the official record. I add the marks AM to the brass cap.

From this same point, a locally established closing corner for secs. 1 and 2, T. 24 S., R. 7 W., bears S. 83° W., 1.225 chs. dist., monumented with a wooden post, 3 ins. sq., 3 ft. long, 6 ins. in the ground, with fragmentary scribe marks visible, from which

A fallen fir, 7 ins. diam., bears S. 14° E., 22 lks. dist., with scribe marks CC S1 T24S R7W BT visible on unhealed blaze.

A fir snag, 25 ins. diam., bears S. $61\frac{1}{2}^{\circ}$ W., 11 lks. dist., with scribe marks CC S2 T24S R7W BT visible on bark.

Descend 520 ft. over SW. slope, changing to W. slope.

38.99 The $\frac{1}{4}$ sec. cor. of sec. 35 only, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

S. $89^{\circ} 12'$ W., beginning new measurement.

Descend 180 ft. over NW. slope, through heavy timber and dense undergrowth.

9.30 Branch, 8 lks. wide, course SW.; asc. 40 ft. over SE. slope.

11.45 Top of ascent, slopes S.; desc. 29 ft. over SW. slope.

14.45 Ravine, drains SE.; asc. 65 ft. over SE. slope.

19.43 Point for the W $1/16$ sec. cor. of sec. 35 only.