

County Surveyor's Record, Douglas County, Oregon

-3-

Dependent Resurvey of a Portion of the S. Bdy., T. 23 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 35
1961

from which

A fir, 13 ins. diam., bears N. $13\frac{1}{4}^{\circ}$ E., 123 lks. dist., mkd. W 1/16 S35 BT.

A fir, 12 ins. diam., bears N. $76\frac{1}{2}^{\circ}$ W., 159 lks. dist., mkd. W 1/16 S35 BT.

Ascend 473 ft. over SE. slope.

35.00 Top of bluff, 190 ft. high, edge bears N. and S.; asc. 103 ft. over steep SE. slope.

38.86 The cor. of secs. 34 and 35 only, perpetuated by the Deputy County Surveyor in 1929, from original corner evidence which is no longer in existence, with a sandstone, 21 x 13 x 6 ins., firmly set, 12 ins. in the ground, mkd. with a cross (+) on top, from which locally established bearing trees:

A fallen black oak, 20 ins. diam., bears N. 49° E., 176 lks. dist., with fragmentary scribe marks visible on decayed face of blaze.

A sawed fir stump, 40 ins. diam., bears N. $83\frac{3}{4}^{\circ}$ E., 130 lks. dist., with scribe marks S3 T23S R7W BT visible on opened double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

FDOK
10/19/93 BY
R. Dolan
M118-17

T 23 S R 7 W
S 34 | S 35
S 2
T 24 S
1961

PROCESSED
10/19/93
R. Dolan

from which new bearing trees:

A black oak, 15 ins. diam., bears N. $19\frac{3}{4}^{\circ}$ E., 149 lks. dist., mkd. T23S R7W S35 BT.

A forked white fir, 70 ins. diam., bears N. $5\frac{1}{2}^{\circ}$ W., 377 lks. dist., mkd. T23S R7W S34 BT.

Deposit the County Surveyor's corner stone alongside the iron post.

From this point the closing corner of secs. 2 and 3, T. 24 S., R. 7 W., bears N. $89^{\circ} 24'$ W., 9.55 chs. dist., perpetuated with a wooden post, 2 x 4 ins. in cross section, 3 ft. long, firmly set, 10 ins. in the ground, from which the original bearing trees:

A sawed fir stump, 42 ins. diam., bears S. 45° E., 9 lks. dist., with a healed blaze.

A broken fir snag, 24 ins. diam., bears S. 70° W., 4 lks. dist., with scribe mark S visible on face of broken blaze.

and locally established bearing trees:

A fir, 22 ins. diam., bears S. 58° E., 61 lks. dist., with a healed double blaze.