

# County Surveyor's Record, Douglas County, Oregon

13072

Dependent Resurvey of a Portion of the S. Bdy., T. 23 S., R. 7 W.

CHAINS	
	<p style="text-align: center;">A fir, 30 ins. diam., bears S. <math>4\frac{1}{2}^\circ</math> W., 85 lks. dist., with a healed double blaze.</p> <p>Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, chinquapin, &amp; madrone. Undergrowth, vine maple, hazel, arrowwood, salmonberry, huckleberry, salal, poison oak, and fern.</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 7 W. (Restoring the 1858 Survey by Thomas H Hutchinson and the 1881 survey by William H. Byars)</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp. N. <math>1^\circ 19'</math> W., bet. secs. 35 and 36, marking and blazing the true line.</p> <p>Descend 78 ft. along broken W. slope, and W. edge of logged area.</p>
32.20	Dry creek bed, 2 lks. wide, drains W.; asc. 58 ft. along broken W. slope.
37.40	Creek, 4 lks. wide, course SW.; asc. 42 ft. over SE. slope.
39.57	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36, determined at record bearing and distance from the original bearing trees:</p> <p style="padding-left: 40px;">A fallen and burned cedar, 23 ins. diam., bears S. <math>20^\circ</math> E., 19 lks. dist., with fragmentary scribe marks visible on burned blaze.</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears S. <math>80^\circ</math> W., 22 lks. dist., with a partly opened blaze, no scribe marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 12 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <math display="block">\begin{array}{c} \frac{1}{4} \\ \text{S } 35   \text{S } 36 \\ \text{T } 23 \text{ S } \text{R } 7 \text{ W} \\ 1961 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. <math>28\frac{1}{4}^\circ</math> E., 34 lks. dist., mkd. <math>\frac{1}{4}</math> S36 BT.</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears N. <math>48\frac{3}{4}^\circ</math> W., 46 lks. dist., mkd. <math>\frac{1}{4}</math> S35 BT.</p>
	<hr style="width: 20%; margin: auto;"/>
	<p>N. <math>0^\circ 39'</math> W., beginning new measurement.</p> <p>Ascend 257 ft. over SE. slope, changing to S. slope.</p>
16.40	Ridge, bears E. and W.; desc. 513 ft. over general NE. slope.
38.73	<p>The cor. of secs. 25, 26, 35, and 36, determined at record bearing &amp; distance from the only remaining original bearing tree:</p> <p style="padding-left: 40px;">A fir, 45 ins. diam., bears S. <math>30^\circ</math> W., 43 lks. dist., with scribe marks BT visible on opened blaze.</p>

FD 11/24/81 M.H.S.