

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 7 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

FOOK
1194 Mills
11/11/11

T 23 S R 7 W
S 26 | S 25
S 35 | S 36
1961

from which

- A cedar, 15 ins. diam., bears N. 66 1/4° E., 42 lks. dist., mkd. T23S R7W S25 BT.
- A cedar, 9 ins. diam., bears S. 49 3/4° E., 49 lks. dist., mkd. T23S R7W S36 BT.
- A fir, 26 ins. diam., bears N. 1° W., 44 lks. dist., mkd. T23S R7W S26 BT.

Land, mountainous.
Soil, sandy clay loam.
Timber, fir, cedar, hemlock, alder, ample. chinquapin, and madrone.
Undergrowth, vine maple, hazel, arrowwood, salmonberry, huckleberry, salal, and fern.

From the cor. of secs. 34 and 35 only, on the S. bdy. of the Tp. N. 0° 12' E., bet. secs. 34 and 35.

Ascend 76 ft. over SW. slope, across nearly open grass land.

9.10 Spur, slopes SW.; desc. 78 ft. over NW. slope.

25.55 Branch, 2 lks. wide, course SW.; asc. 166 ft. over SE. slope.

38.89 Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

1/4
S 34 | S 35
T 23 S R 7 W
1961

from which

- A white fir, 20 ins. diam., bears N. 28° E., 126 1/2 lks. dist., mkd. 1/4 S35 BT.
- A white fir, 20 ins. diam., bears N. 74 1/4° W., 63 lks. dist., mkd. 1/4 S34 BT.

Ascend 34 ft. over SE. slope.

47.20 Ridge, bears NE., turning to E. and SW., turning to W., also dirt road, 20 lks. wide, bears Same as ridge; desc. 490 ft. over precipitous N. slope, across logged land.

58.71 Point for the N 1/16 sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.