

## County Surveyor's Record, Douglas County, Oregon

-10-

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 7 W.

CHAINS	<p style="text-align: center;">Wilford N. Haines 239 Survey Point Drain, Ore.</p> <p>Ascend 4 ft. over general W. slope.</p> <p>42.40 Branch, 4 lks. wide, course SW.; asc. 334 ft. over general SW. slope.</p> <p>60.93 Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 22   S 23 1961</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 75½° E., 44½ lks. dist., mkd. N 1/16 S23 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 67° W., 34½ lks. dist., mkd. N 1/16 S22 BT.</p> <p>From this point a corner established by Wilford N. Haines, bears S 3° 10' E., 0.725 chs. dist., monumented with a 1 in. T. iron, firmly set, projecting 8 ins. above ground, with an aluminum cap mkd.</p> <p style="text-align: center;">Wilford N. Haines 239 Survey Point Drain, Ore.</p> <p>from which</p> <p style="padding-left: 40px;">A white oak, 12 ins. diam., bears N. 22½° E., 71½ lks. dist., with scribe marks 1/16 S23 BT visible on unhealed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 35° E., 68½ lks. dist., with scribe marks 1/16 S23 BT visible on unhealed blaze.</p> <p>Ascend 3 ft. over SW. slope.</p> <p>61.20 Spur, slopes W.; desc. 100 ft. over NW. slope.</p> <p>64.45 Branch, 2 lks. wide, course W.; asc. 40 ft. over SW. slope.</p> <p>66.80 Spur, slopes SW.; desc. 17 ft. over NW. slope.</p> <p>68.00 Branch, 2 lks. wide, course SW.; asc. 376 ft. over S. slope.</p> <p>81.24 The cor. of secs. 14, 15, 22, and 23, monumented with a private surveyor's iron pipe, 36 ins. long, 1½ in. diam., lying on the ground with brass cap mkd: LS 307 T23S R7W S14 S15 S22 and S23 1957, at record bearing and distance from the only remaining original bearing tree:</p> <p style="padding-left: 40px;">A black oak, 54 ins. diam., bears N. 33° W., 114 lks. dist., with fragmentary scribe marks visible on decayed face of blaze. (Byars, 1881). This tree has also been bark scribed T23S R7W S15 BT on the SE. and LS 363 on the S. face.</p>
--------	---