

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 7 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 7 W
S 15 S 14
S 22 S 23
1961

from which

A black oak, 6 ins. diam., bears N. 21° E., 19 lks. dist., with scribe marks T23S R7W S14 BT visible on unhealed blaze. (Mkd. by Haines in 1949).

and new bearing trees:

A fir, 16 ins. diam., bears S. 39° E., 136 lks. dist., mkd. T23S R7W S23 BT.

A black oak, 10 ins. diam., bears S. 53° W., 130 lks. dist., mkd. T23S R7W S22 BT.

Deposit the private surveyor's iron pipe, alongside the iron post.

From this point a locally established corner, bears N. 57° E., 0.125 chs. dist., monumented with a 1 in. T. iron, firmly set, projecting 14 ins. above ground, with an aluminum cap mkd.

Wilford N. Haines
 239
 Survey
 Point
 Drain Ore.

There is no remaining evidence of any of the original meander corners which were established on this mile of line.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, cedar, hemlock, alder, maple, oak, chinquapin, madrone. Undergrowth, vine maple, hazel, arrowwood, slamonberry, huckleberry, blackberry, salal, poison oak, and fern.

From the cor. of secs. 26, 27, 34, and 35.

N. 88° 52' W., bet. secs. 27 and 34.

Descent 112 ft. over NW. slope, along the N. edge of logged area.

7.10 Branch, 1 lk. wide, course N. 20° W.; asc. 35 ft. over NE. slope.

8.40 Spur, slopes N.; desc. 52 ft. over NW. slope.

10.00 Branch, 2 lks. wide, course N.; asc. 251 ft. over NE. slope, changing to precipitous N. slope.

37.75 Spur, slopes N.; desc. 63 ft. over NW. slope.

40.145 Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.