

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to solid rock, with brass cap mkd.

1/4 S 27  
S 34  
T 23 S R 7 W  
1961

from which

A chinquapin, 15 ins. diam., bears N. 60 1/2° E., 70 lks. dist., mkd. 1/4 S27 BT.

A fir, 18 ins. diam., bears S. 72 1/2° E., 170 lks. dist., mkd. 1/4 S34 BT.

Descent 266 ft. over NW. slope, chainging to W. slope.

58.40 Branch, 2 lks. wide, course N. 30° W.; asc. 320 ft. over NE.slope.

68.35 Spur, slopes N. 15° W.; desc. 120 ft. over NW. slope.

77.05 Ravine, drains N. 20° W.; asc. 47 ft. over E. slope.

78.20 Spur, slopes N.; desc. 40 ft. over NW. slope.

80.29 Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 7 W  
S 28 | S 27  
S 33 | S 34  
1961

*Fd. by :*  
*DON BENTZ*  
*3/83*

from which

A madrone, 11 ins. diam., bears N. 18° E., 64 lks. dist., mkd. T23S R7W S27 BT.

A maple, 18 ins. diam., bears S. 53 1/2° E., 168 lks. dist., mkd. T23S R7W S34 BT.

A white fir, 8 ins. diam., bears S. 78 1/2° W., 224 lks. dist., mkd. T23S R7W S33 BT.

A white fir, 15 ins. diam., bears N. 84 1/2° W., 148 lks. dist., mkd. T23S R7W S28 BT.

From this point the 1/4 sec. cor. of secs. 33 and 34, bears S. 0° 58' E., 40.32 chs. dist., determined at record bearing and distance from the only remaining original bearing tree:

A white oak, 35 ins. diam., bears S. 9° E., 312 lks. dist., with rotted blaze showing axe marks but no scribe marks.

At the corner point

Set an iron post 28 ins. long 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 23 S R 7 W  
S 33 | S 34  
1961

from which

*M 90-38 A E B*  
*BLM 1983*  
*Survey Vol. 44*  
*Pg. 17608*  
*1961*