

# County Surveyor's Record, Douglas County, Oregon

-13-

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 7 W.

CHAINS	
	<p>A fir, 8 ins. diam., bears N. <math>5\frac{1}{2}^{\circ}</math> E., 136 lks. dist., mkd. <math>\frac{1}{4}</math> S34 BT.</p> <p>A fir, 15 ins. diam., bears N. <math>12\frac{3}{4}^{\circ}</math> W., 121 lks. dist., mkd. <math>\frac{1}{4}</math> S33 BT.</p> <p>From this same point the meander cor. of secs. 30 and 31 on the left bank of the Umpqua River, bears N. <math>89^{\circ} 40'</math> W., 173.27 chs. dist., determined at record bearing and distance from the only remaining original bearing tree:</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears N. <math>44^{\circ}</math> W., 27 lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, and in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} T\ 23\ S\ R\ 7\ W \\ \begin{array}{l} S\ 30 \\ S\ 31 \end{array} \diagdown \\ \qquad \qquad \qquad MC \\ \qquad \qquad \qquad 1961 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. <math>58\frac{1}{2}^{\circ}</math> W., <math>30\frac{1}{2}</math> lks. dist., mkd. T23S R7W S31 MC BT.</p> <p>Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, chinquapin, and madrone. Undergrowth, vine maple, huckleberry, hazel, arrowwood, salal, poison oak, and fern.</p>
	<p>N, <math>0^{\circ} 11'</math> E., bet. secs. 27 and 28.</p> <p>Ascend 4 ft. along W. slope and edge of logged area.</p>
0.50	Top of ascent, slopes W.; desc. 534 ft. over precipitous N. slope.
4.13	Point for the S. meander cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.
8.69	From this point, chisel marks S/L on face of ledge bears East, 0.05 chs. dist.
9.00	Dirt road, 20 lks. wide, bears E. and W.
10.30	Point for a witness point of secs. 27 and 28.
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} W\ P \\ S\ 28\   \ S\ 27 \\ \qquad \qquad \qquad 1961 \end{array}</math> </div> <p style="padding-left: 40px;">No suitable bearing trees available.</p> <p>Descend 3 ft. over N. slope.</p>
10.90	Right bank of Umpqua River, bears E. and W., course E.
17.30	Left bank of Umpqua River; asc. 270 ft. over general SE. slope, also enter pasture land.
20.30	Maupin Road, gravel surfaced, 25 lks. wide, bears E. and W.