

County Surveyor's Record, Douglas County, Oregon

-14-

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 7 W.

CHAINS
40.32

The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, perpetuated by the County Surveyor in 1925, with a sandstone, 24 x 4 x 4 ins., firmly set, 12 ins. in the ground, mkd. with a cross (+) on top, 27 on the east, 28 on the west, and $\frac{1}{4}$ on the south face, from which the remaining original bearing tree:

A fallen and burned oak, 22 ins. diam., bears N. 45° W.,
66 lks. dist., with no marks remaining.

and trees mkd. by the County Surveyor:

A burned and rotted white fir snag, 20 ins. diam.,
bears N. 67° E., 22 $\frac{1}{2}$ lks. dist., with scribe marks
BT visible on decayed face of blaze.

A sawed fir stump, 26 ins. diam., bears N. 67° W.,
39 lks. dist., with scribe marks BT visible on bark.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 28 | S 27
 T 23 S R 7 W
 1961

from which

A white oak, 12 ins. diam., bears S. 58° E., 80 lks. dist.,
mkd. $\frac{1}{4}$ S27 BT.

A fir, 10 ins. diam., bears S. 7° W., 52 lks. dist.,
mkd. $\frac{1}{4}$ S28 BT.

The corner falls on a barbed wire fence line, extending generally N. and S.

N. 0° 06' E., beginning new measurement.

Ascend 350 ft. over general S. slope.

40.17

The cor. of secs. 21, 22, 27 and 28, monumented with the original oak post, 5 x 6 ins., in cross section, 24 ins. long, firmly set, 8 ins. in the ground, with fragmentary scribe marks visible, from which the remaining original bearing tree:

A white oak, 50 ins. diam., bears N. 65° E., 77 lks.
dist., with burned blaze.

and trees mkd. by the County Surveyor in 1925:

A stump hole, bears S. 75° E., 21 lks. dist.

A white oak, 50 ins. diam., bears S. 71° W., 149 lks.
dist., with a healed double blaze.

A fir, 25 ins. diam., bears N. 80 $\frac{1}{2}$ ° W., 79 lks. dist.,
with a healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.