

## County Surveyor's Record, Douglas County, Oregon

-16-

Subdivision of Section 35, T. 23 S., R. 7 W.

CHAINS

40.50

Bottom of descent, slopes W.; asc. 98 ft. over SW. slope.

53.30

Ridge, bears E. and W.; desc. 221 ft. over steep N. slope.

58.915

Point for the center N 1/16 sec. cor. of sec. 35.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

C  
N 1/16 S 35  
C  
1961

from which

A fir, 41 ins. diam., bears N. 32½° E., 65 lks. dist., mkd. CN 1/16 S35 BT.

A fir, 8 ins. diam., bears N. 68¼° W., 114 lks. dist., mkd. CN 1/16 S35 BT.

The corner falls at edge of timber, edge bears E. and W.

Descend 524 ft. over N. slope.

78.41

The ¼ sec. cor. of secs. 26 and 35.

From the ¼ sec. cor. of secs. 35 and 36.

S. 88° 27' W., along the E. and W. center line of sec. 35.

Ascend 48 ft. over SE. slope, through heavy timber and dense undergrowth.

2.70

Spur, slopes S.; desc. 155 ft. over SW. slope.

9.20

Branch, 3 lks. wide, course S.; asc. 649 ft. over SE. slope.

34.70

Spur, slopes SW., also leave timber, enter logged area, edge bears N. and S.; desc. 82 ft. over NW. slope.

39.54

The center ¼ sec. cor. of sec. 35.

Descend 196 ft. over NW. slope.

57.50

Branch, 2 lks. wide, course SW.; desc. 2 ft. along general S. slope.

58.27

Point for the center W 1/16 sec. cor. of sec. 35.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

W 1/16  
C ————— C  
S 35  
1961

from which

A fir, 8 ins. diam., bears N. 52° W., 112 lks. dist., mkd. CW 1/16 S35 BT.

A fir, 8 ins. diam., bears S. 47½° W., 61½ lks. dist., mkd. CW 1/16 S35 BT.