

County Surveyor's Record, Douglas County, Oregon

-2-

Dependent Resurvey of a Portion of the E. Bdy., T. 21 S., R 6 W.

CHAINS

from which the remains of an 1884 bearing tree,

A sawed fir stump, 20 ins. diam., which has slid down hill approximately 6 lks., the stump hole of which bears N. 22° W., 17 lks. dist., mkd. S1 on open blaze.

trees mkd by County Surveyor:

A fir, 30 ins. diam., bears S. 86½° E., 15 lks, dist., mkd. S6 BT on partially healed blaze.

A fir, 24 ins. diam., bears S. 47 3/4° E., 22 lks. dist., mkd. S on partially healed blaze.

A fir, 14 ins. diam., bears S. 17° W., 31 lks. dist., mkd. S12 BT on partially healed blaze.

and new bearing trees:

A fir, 48 ins. diam., bears S. 14° E., 79 lks. dist., mkd. T2LS R5W S7 BT.

A fir, 62 ins. diam., bears S. 45° W., 72 lks. dist., mkd. T2LS R6W S12 BT.

A fir, 4 ins. diam., bears N. 18° W., 47 lks. dist., mkd. XBT.

I stamp USFJH 1962 on brass cap.

N. 0° 46' W., bet. secs. 1 and 6, marking and blazing the true line.

Ascend 14 ft. over SW. slope, through logged area.

- 0.55 Dirt road, 12 lks. wide, bears E. and W.; asc. 35 ft. through logged area and dense undergrowth.
- 2.70 Spur, slopes W.; desc. 15 ft. over NW slope.
- 3.60 Dirt road, 10 lks. wide, bears E. and W.; desc. 20 ft. over NW slope.
- 4.30 Dirt road, 12 lks. wide, bears E. and W.; desc. 71 ft. over NW slope.
- 6.15 Dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.; desc. 112 ft. over NW slope.
- 9.10 Creek, 3 lks. wide, course S. 75° W.; asc. 45 ft. over broken SW slope.
- 10.00 Spur, slopes W.; desc. 65 ft., over NW slope.
- 12.50 Creek, 2 lks. wide, course W.; asc. 29 ft. over SW slope.
- 16.30 Top of ascent, slopes W.; desc. 122 ft. over NW slope.
- 19.94 Point for the 3 1/16 sec. cor. of secs. 1 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground with brass cap mkd.

S 1/16
S1 | S6
1962

from which