

County Surveyor's Record, Douglas County, Oregon

-5-

Dependent Resurvey of a Portion of the E. Bdy., T. 21 S., R. 6 W.

CHAINS

A fir, 16 ins. diam., bears N. 6° E., 80 lks. dist., mkd.
T20S R5W S31 BT.

A fir, 16 ins. diam., bears S. 59° E., 54 lks. dist., mkd.
T21S R5W S6 BT.

A fir, 6 ins. diam., bears S. 37° W., 151 lks. dist., mkd.
T21S R6W S1 BT.

A fir, 6 ins. diam., bears N. 22° W., 165 lks. dist., mkd.
T20S R6W S36 BT.

I stamp USBLM 1962 on brass cap.

Corner falls at W. edge of dirt road, 15 lks. wide, bears N. and S.

Land, rolling hills.

Soil, clay, loam.

Timber, fir, cedar, hemlock, maple, chinquapin, madrone, alder,
willow, and dogwood; undergrowth, vine maple, arrowwood, manzanita,
hazel, and poison oak.

Dependent Resurvey of a Portion of the South Boundary
of
T. 20. S., R. 6 W.

(Restoring the 1872 survey by J. H. McClung)

From the cor. of Tps. 20 and 21 S., Rs. 5 and 6 W.

S. 89° 52' W., along the S. bdy. of sec. 36.

Ascend 15 ft. over NE. slope, through logged area.

2.50 Spur, slopes S.; desc. 62 ft. over SW slope.

3.60 Bottom of descent; asc. 11 ft. over SE. slope.

10.15 Spur slopes S.; desc. 53 ft. over SW slope.

13.30 Dirt road, 12 lks. wide, bears N. 40° W. and S. 40° E.; desc. 65 ft.
over SW. slope.

15.30 Creek, 2 lks. wide, course S.; asc. 52 ft. over broken E. slope.

19.00 Creek, 1 lk. wide, course S. 60° E.; asc. 10 ft. over E. slope.

19.70 Point for the E 1/16 sec. cor of sec. 1 only, on the N bdy. of T.21
S., R. 6 W.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in ground,
with brass cap mkd.

E 1/16 S1
1962

from which

A fir, 24 ins. diam., bears S. 23 3/4° E., 146 lks. dist., mkd.
E 1/16 S1 BT.

A fir, 24 ins. diam., bears S. 74½° W., 100 lks, dist., mkd.
E 1/16 S1 BT.