


Dependent Resurvey of a Portion of the S. Bdy. T. 20 S. R. 6 W.

| CHAINS | |
|--------|--|
| | Ascend 15 ft. over E. slope. |
| 20.80 | Same dirt road, 12 lks. wide, bears N. 60° E. and S. 60° W.; asc. 131 ft. over E. slope. |
| 29.10 | Ridge, bears N. and S.; desc. 37 ft. over W. slope. |
| 30.75 | Same dirt road, 12 lks. wide, bears N. 25° W. and S. 25° E.; desc. 156 ft. over W. slope. |
| 36.35 | Creek, 2 lks. wide, course S.; asc. 25 ft. over SE slope. |
| 39.40 | Point for the $\frac{1}{4}$ sec. cor. of Sec. 1 only, T. 21 S., R. 6 W.; herein after described. |
| 40.86 | Point for the $\frac{1}{4}$ sec. cor. of sec. 36 only, at proportionate distance there is no remaining evidence of the original corner. No permanent monument established. |
| | Ascend 23 ft. over SE. slope. |
| 42.40 | Top of ascent on rolling land; desc. 25 ft. over W. slope. |
| 45.65 | Same dirt road, 12 lks. wide, bears N. 45° E. and W.; asc. 49 ft. over broken SE. slope, along road. |
| 54.30 | Ridge, bears N. 35° E. and S. 35° W.; leave dirt road, 12 lks. wide, bears N. 35° W., curving to W.; desc. 108 ft. over broken NW. slope. |
| 65.00 | Ravine, drains N.; asc. 100 ft. over NE. slope. |
| 70.95 | Ridge, bears N. 30° W. and S 30° E.; desc. 171 ft. over SW. slope. |
| 77.90 | Ravine, drains N. 40° W.; asc. 40 ft. over NE slope. |
| 78.80 | Point for the closing cor. of secs. 1 and 2, T. 21 S., R 6 W., hereinafter described. |
| | Ascend 10 ft. over NE slope. |
| 81.72 | The cor. of secs. 35 and 36, which has been perpetuated with a Douglas County survey marker, an iron post, 1 in. diam., protruding 8 ins. from the ground, firmly set, with brass cap mkd. |



from which the remaining original bearing trees:

A sawed fir stump, 26 ins. diam., bears N. 65 3/4° E., 25 lks. dist., mkd. BT on opened face, (Record bearing, N. 17 1/2° E)

A fir snag, 48 ins. diam., bears S. 45° E., 38 lks. dist., mkd. BT on open blaze.

A rotted fir stub, bears S. 24 3/4° W., 20 lks. dist., mkd. BT. (Not of record)

trees mkd. by the County Surveyor:

A fir, 12 ins. diam., bears N. 54° E., 68 lks. dist., mkd. S36 T20S R6W CS BT.