

Dependent Resurvey of a Portion of the S. Bdy., T. 20 S., R. 6 W.

CHAINS

A fir, 16 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ W., 18 lks. dist., mkd. S35 T20S R6W CS BT.

and new bearing trees:

A fir, 12 ins. diam., bears N. 51° E., 75 lks. dist., mkd. T20S R6W S36 BT.

A fir, 24 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ W., 33 lks. dist., mkd. T20S R6W S35 BT.

I stamp USBLM 1962 on brass cap.

Land, mountainous.

Soil, clay, loam.

Timber, fir, cedar, hemlock, maple, chinquapin, madrone, alder, willow, and dogwood; undergrowth, vine maple, arrowwood, manzanita, hazel, and poison oak.

Dependent Resurvey of a Portion of the Subdivisional Lines
of
T 21 S., R. 6 W.

(Restoring the 1884 survey by William P. Wright)

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.
S. $88^{\circ} 39'$ W., bet. secs. 1 and 12.

Descend 117 ft. over SW. slope, through logged area and dense brush.

- 5.30 Bottom of steep descent; desc. slightly over W. slope.
 - 5.60 Smith River Road, 40 lks. wide, bears N. and S.
 - 6.00 Barbed wire fence, bears N. and S.
 - 6.90 Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.; desc. 26 ft. over W. slope.
 - 9.85 Smith River, 15 lks. wide, course N. 30° E.; asc. 30 ft. in ravine, course E.
 - 11.80 Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.; asc. 60 ft. in same ravine.
 - 16.20 Barbed wire fence, bears N. and S.
 - 16.25 Dirt road, 12 lks. wide, bears N. and S.; asc. 20 ft. in same ravine.
 - 18.40 Leave ravine, course E. from N. 80, W.; asc. 43 ft. over NE slope.
 - 20.45 Point for the E 1/16 sec. cor. of secs. 1 and 12.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam, 26 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S1}{S12}$

1962

from which

A fir, 5 ins. diam., bears N. 38° E., 58 lks. dist., mkd E 1/16 S1 BT.