

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 21 S.R. 6 W.

CHAINS

A fir, 6 ins. diam., bears S. 30° E., 52 lks. dist., mkd E 1/16 S12 BT.

Ascend 320 ft. over NE slope.

40.90 The 1/4 sec. cor. of secs. 1 and 12, determined from the remaining original bearing tree:

A sawed fir stump, 28 ins. diam., bears S. 45° W., 27 lks. dist., mkd. / S on opened blaze.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T21SR6W	
1/4	S1
-----	
S12	

1962

from which

A maple, 17 ins. diam., bears N. 11° W., 39 lks. dist., mkd. 1/4 S1 BT.

A fir, 8 ins. diam., bears S. 39° E., 60 lks. dist., mkd. 1/4 S12 BT.

S. 88° 49' W., beginning new measurement.

Ascend 25 ft. over E. slope, through dense undergrowth.

0.80 Spur, slopes N.; asc. 60 ft. over broken N. slope.

6.15 Spur, slopes NW.; desc. 90 ft. over NW. slope.

10.30 Ravine, drains N. 30° W.; asc. 25 ft. over NE. slope.

14.50 Ridge, bears N. 30° W. and S. 30° E.; desc. 250 ft. over SW slope.

25.60 Ravine, drains S. 30° W.; asc. 15 ft. over SE slope.

30.25 Dirt road, 15 lks. wide, bears N. 75° E. and S. 75° W.; spur slopes SW.; desc. 20 ft. over NW slope.

32.75 Same dirt road, bears N. 45° W. and S. 45° E.; desc. 120 ft. over NW slope.

33.15 Ravine, drains S. 25° W.; asc. 105 ft. over SE slope.

38.70 Spur, slopes S.; desc. 10 ft. over SE. slope.

38.79 The cor. of secs. 1, 2, 11 and 12, which has been perpetuated with a Douglas County survey marker, an iron post, 1 in. diam., protruding 8 ins. from the ground, firmly set, with brass cap mkd.

T21SR6W

S2	S1
S11	S12

1961

*FD. OK 12/92  
L. ROBERTS  
M 116-23  
C.S. 63/199*

from which the remains of the original bearing trees:

A rotted fir stump, size indeterminate, bears N. 74° E., 17 lks. dist., with no marks remaining.