

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 21 S.R. 6 W.

CHAINS

36.90 Smith River Road, 30 lks. wide, gravelled, bears E. and W.; asc 50 ft. over S. slope.

40.05 Point for the $\frac{1}{4}$ sec. cor. of sec. 1 and 2, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21SR6W

S2 | S1

1962

*L. ROBERTS
FD OK
12/1992
M116-43
as being*

from which

A fir, 50 ins. diam., bears S. 57° E., 112 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

A fir, 6 ins. diam., bears N. 60° W., 74 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

A 1 in. "T" iron, firmly set, protruding 6 ins. from the ground, bears S. 23° W., 5 lks. dist.

Ascend 236 ft. over general S. slope, changing to SE. slope.

58.70 Ridge, bears E. and W.; desc. 35 ft. over N. slope.

60.07 Point for the N $1/16$ sec. cor. of secs. 1 and 2.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

N $1/16$

S2 | S1

1962

FD OK BY L. ROBERTS
12/1992 M116-43 C.S. 63/149-3E

from which

A fir, 25 ins. diam., bears N. $50\frac{1}{2}^\circ$ E., 87 lks. dist., mkd. N $1/16$ S1 BT.

A fir, 25 ins. diam., bears N. 79° W., 95 lks. dist., mkd. N $1/16$ S2 BT.

A 1 in. "T" iron, firmly set, protruding 14 ins. from the ground, bears West, 5 lks. dist.

Descend 155 ft. over N. slope.

64.25 Creek, 1 lk. wide, course W.; asc 53 ft. over S. slope.

66.50 Spur, slopes SW.; desc. 67 ft. over NW. slope.

68.90 Creek, 2 lks. wide, course S. 45° W.; asc. 143 ft. over SE. slope.

79.85 Ridge, bears E. and W.; desc. slightly over NE. slope.

81.58 Point for the closing cor. of secs. 1 and 2, at intersection with the S. bdy. of sec. 36, T. 20 S., R. 6 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.