

County Surveyor's Record, Douglas County, Oregon

-12-

Dependent Resurvey of Portion of Subdivisional Lines of T. 21 S., R. 6 W.

CHAINS

$\frac{1}{4}$ Sl
 T21S R6W
 1962

from which

A fir, 26 ins. diam., bears S. $6\frac{1}{2}^{\circ}$ E., 70 lks. dist., mkd.
 $\frac{1}{4}$ Sl BT.

A fir, 52 ins. diam., bears S. 46° W., 91 lks. dist., mkd.
 $\frac{1}{4}$ Sl BT.

Subdivision of Section 1, T. 21 S., R. 6 W.

The following subdivision of section 1 was executed in conformity with legal surveying practice. The record of true line notes, only, is set forth in the following field notes.

From the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.

N. $0^{\circ} 24'$ E., on the N. and S. center line of sec. 1.

Descend 213 ft. over broken NE. slope, through scattering timber and dense undergrowth.

20.00 Point for the center $\frac{1}{16}$ sec. cor. of sec. 1.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap mkd.

$\frac{1}{16}$ Sl
 S $\frac{1}{16}$ Sl
 1962

from which

A fir, 20 ins. diam., bears S. 6° E., 49 lks. dist., mkd.
 $\frac{1}{16}$ Sl BT.

A fir, 6 ins. diam., bears S. 33° W., 59 lks. dist., mkd.
 $\frac{1}{16}$ Sl BT.

Descend 300 ft. over NE slope, through medium timber.

Enter bottom; edge bears N. 85° W. and S. 85° E.

30.30 Thence over nearly level land.

30.90 Smith River, 20 lks. wide, course N. 50° W.; continue across nearly level land.

31.15 Creek, 2 lks. wide, course W.; continue across nearly level land.

37.55 Leave bottom; asc. 45 ft. over S. slope.

40.00 Point for the center $\frac{1}{4}$ sec. cor. of sec. 1, at intersection with the E. and W. center line.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ Sl

1962