

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 1, T. 21 S. R. 6 W

CHAINS	
17.00	Dirt road, 12 lks. wide, bears N. and S.; asc. 10 ft. over E. slope.
17.80	Top of ascent, slopes S.; desc. 8 ft. over SW. slope.
20.03	Point for the center E. 1/16 sec. cor. of sec. 1.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground with brass cap mkd.
	$C \frac{E \ 1/16}{S1} C$ 1962
	from which
	A fir, 32 ins. diam., bears N. 70° E., 170 lks. dist., mkd. CE 1/16 S1 BT.
	A fir, 7 ins. diam., bears S. 7 3/4° E., 137 lks. dist., mkd. CE 1/16 S1 BT.
	Descend 25 ft. over SW. slope.
26.30	Two wire power line, bears N. 50° W. and S. 50° E.; desc. 73 ft. over SW. slope.
37.35	Creek 2 lks. wide, course S.; asc. 15 ft. over SE slope.
38.00	Smith River Road, gravelled, 40 lks. wide, bears N. 50° W. and S. 50° E.; asc. 10 ft. over cut.
40.05	The center ¼ sec. cor. of sec. 1.
	Ascend slightly over gentle SE slope.
42.15	Top of ascent, slopes S.; desc. 40 ft. over SW. slope.
50.45	Smith River Road, 40 lks. wide, bears N. 70° E. and S. 70° W.; asc. 11 ft. over SE. slope.
62.60	Barbed wire fence, bears N. and S.; asc. 35 ft. over SE. slope.
66.75	Low spur, slopes S.; desc. 14 ft. over E. slope.
69.05	Creek, 1 lk. wide, course S.; asc. 63 ft. over E. slope.
72.60	Spur, slopes S.; desc. 28 ft. over SW. slope.
79.15	The ¼ sec. cor. of secs. 1 and 2.
	Land, rolling hills. Soil, loam and clay. Timber, fir, cedar, hemlock, maple, chinquapin, madrone, alder, willow, and dogwood; undergrowth, vine maple, arrowwood, manzanita, hazel, and poison oak.
	From the center E. 1/16 sec. cor. of sec. 1.
	N. 0° 04' W., on the N. and S. center line of the NE¼ of sec. 1.
	Ascend 220 ft. over S. slope through scattering timber, fir reproduction and dense undergrowth.
14.00	Slope changes; asc. slightly along E. slope.
20.05	Point for the NE 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the NE¼.