

County Surveyor's Record, Douglas County, Oregon

-2-

Dependent Resurvey of a Portion of the S. Bdy., T. 22 S., R. 8 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 8 W
S 33/S34
 S 4
 T 23 S
 1962

from which new bearing trees

A white oak, 18 ins. diam., bears N. 22° E., 54 lks. dist., marked T22S R8W S34 BT.

A white oak, 12 ins. diam., bears N. 64° E., 33 lks. dist., marked X BT.

No suitable bearing tree available in section 33.

Reset fence corner post alongside the iron post.

N. 89° 26' W., along the S. bdy. of sec. 33, marking and blazing the true line.

Ascend 28 ft. over gentle SE. slope, across open pasture land.

0.20 Graveled road, 15 lks. wide, bears N. and S.

9.80 Top of ascent, slopes S.; desc. 19 ft. over SW. slope.

15.15 Creek, 2 lks. wide, course S.; asc. 31 ft. over SE. slope.

22.00 Top of ascent, slopes S.; desc. 200 ft. over SW. slope.

22.50 Leave pasture, enter legged area, edge bears N. and S.

35.40 Creek, 4 lks. wide, course S. 30° E.; asc. 113 ft. over NE. slope.

39.95 Point for the ¼ sec. cor. of sec. 33 only at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T 22 S R 8 W
¼ S 33
 1962

from which

A fir, 4 ins. diam., bears N. 76½° E., 38½ lks. dist., marked ¼ S33 BT.

A fir, 12 ins. diam., bears N. 6° W., 32 lks. dist., marked ¼ S33 BT.

Ascend 147 ft. over general E. slope.

59.40 Spring seepage, drains S.; thence over level land.

59.925 Point for the W 1/16 sec. cor. of sec. 33 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

W 1/16 S 33
 1962