

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the S. Bdy., T. 22 S., R. 8 W.

CHAINS

from which

A fir, 3 ins. diam., bears N. 72° E., 194 lks. dist., marked X BT.

A white fir, 18 ins. diam., bears N. 67½° W., 22 lks. dist., marked W 1/16 S33 BT.

Corner falls at edge of old logged area, edge bears N. and S.

Ascend 332 ft. over steep E. slope, through heavy timber and dense undergrowth.

70.90 Ridge, bears N. and S.; desc. 279 ft. over steep W. slope.

76.92 Point for the closing cor. of secs. 4 & 5, T. 23 S., R. 8 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S
S 33
 S 5/S 4
 C C
 T 23 S R 8 W
 1962

from which

A fir, 8 ins. diam., bears S. 20° E., 94 lks. dist., marked T23S R8W S4 CC BT.

A white fir, 11 ins. diam., bears S. 62° W., 55 lks. dist., marked T23S R8W S5 CC BT.

Descend 20 ft. over SW. slope.

79.90 Point for the cor. of secs. 32 and 33 only, at proportionate dist.; there is no remaining evidence of the original corner point.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 8 W
S 32/S 33
 S 5
 T 23 S
 1962

from which

A fir, 25 ins. diam., bears N. 5½° E., 16½ lks. dist., marked T22S R8W S33 BT.

A white fir, 18 ins. diam., bears N. 20½° W., 73 lks. dist., marked T22S R8W S32 BT.

Corner falls at bottom of descent, slopes S.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, alder, madrone, myrtle and chinquapin; undergrowth, vine maple, hazel, arrowwood, huckleberry, salmonberry, blackberry, poison oak, and fern.