

County Surveyor's Record, Douglas County, Oregon

-4-

Dependent Resurvey of a Portion of the S. Bdy., T. 22 S., R. 8 W.

CHAINS

N. 89° 26' W., along the S. bdy. of section 32.

Ascend 18 ft. along gentle S. slope, through heavy timber and dense undergrowth.

7.00 Top of ascent, slopes S.; desc. 109 ft. over SW. slope.

24.85 Bottom of descent, slopes S.; asc. 35 ft. over SE. slope.

28.90 Spur, slopes S.; desc. 79 ft. over SW. slope.

38.20 Spur, slopes S. 60° W.; desc. 37 ft. along N. slope.

39.95 The $\frac{1}{4}$ sec. cor. of sec. 32 only, determined at record distance from the original bearing trees:

A fir, 52 ins. diam., bears N. 35° E., 27 lks. dist., with no marks remaining on badly scaled bark blaze.
(Record bearing, N. 30° E.)

A fir, 28 ins. diam., bears South, 9 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on the bark.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 8 W
 $\frac{1}{4}$ S 32
T 23 S
1962

FR. OK. by:
R.R. LUCKMAN
6-10-82
M 92-54

from which new bearing trees

A chinquapin, 5 ins. diam., bears N. 46 $\frac{1}{2}$ ° E., 48 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S32 BT.

A fir, 6 ins. diam., bears N. 15 $\frac{1}{2}$ ° W., 37 lks. dist., marked $\frac{1}{4}$ S32 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, alder, madrone, myrtle and chinquapin; undergrowth, vine maple, hazel, arrowweed, huckleberry, salmonberry, poison oak and fern.

DEPENDENT RESURVEY of a Portion of the Subdivisional lines,
T. 22 S., R. 8 W.

(Restoring the 1855 survey by Harvey Gordon and Charles T. Gardner and the 1881 survey by William H. Byars.)

From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp.

N. 0° 10' E., bet. secs. 33 and 34, marking and blazing the true line.

Ascend 49 ft. over gentle S. slope across open pasture land, along woven wire fence and E. edge of graveled road, 15 lks. wide.

0.70 Power line, 2 wires, bears N. 50° E. and S. 50° W.

6.00 Power line, 2 wires, bears N. 55° W. and S. 55° E.

7.40 Top of ascent, slopes E.; also leave edge of road, bears N.W. and S., continue along fence; desc. 92 ft. over NE. slope.