

County Surveyor's Record, Douglas County, Oregon

-6-

DEpendent Resurvey of a Portion of the Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS

from which

A fir, 10 ins. diam., bears N. 49° E., 45 lks. dist.,
marked T22S R8W S27 BT.

A fir, 12 ins. diam., bears S. $72\frac{1}{2}^{\circ}$ E., 61 lks. dist.,
marked T22S R8W S34 BT.

A white oak, 16 ins. diam., bears S. 66° W., 43 lks.
dist., marked T22S R8W S33 BT.

A fir, 6 ins. diam., bears N. 12° W., 62 lks. dist.,
marked T22S R8W S28 BT.

From this point the original witness point established by Godron
and Gardner in 1855, on the line bet. secs. 27 and 28, bears N. 0°
 $59'$ W., 30.23 chs. dist., perpetuated and recorded by the Douglas
County Surveyor in 1961, monumented with an iron post, $1\frac{1}{2}$ ins. diam.,
firmly set, projecting 18 ins. above ground, with brass cap
marked

COUNTY SURVEYOR'S OFFICE

T 22 S R 8 W
W C
S 28 | S 27
1961

from which the original bearing trees

A rotted fir stump, 26 ins. diam., bears S. $78\frac{3}{4}^{\circ}$ E.,
78 lks. dist., with scribe marks BT visible on
opened blaze. (Record bearing, S. 77° E.)

A fir, 53 ins. diam., bears S. $58\frac{1}{2}^{\circ}$ W., 26 lks. dist.,
with scribe marks S 28 2S T visible on bark.
(Record bearing, S. 54° W.)

and a tree marked by the County Surveyor

A fir, 9 ins. diam., bears N. $34\frac{1}{2}^{\circ}$ E., $18\frac{1}{2}$ lks. dist.,
with scribe marks WC S27 CS BT visible on unhealed
double blaze.

I add the marks ELC 1962 to the brass cap.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, alder, maple, oak, madrone, myrtle
and chinquapin; undergrowth, vine maple, hazel, arrowwood,
huckleberry, salmonberry, blackberry, poison oak, wild rose,
and fern.