

County Surveyor's Record, 8 Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS	<p>A fir, 4 ins. diam., bears S. <math>38\frac{1}{2}^{\circ}</math> W., 84 lks. dist., marked <math>\frac{1}{4}</math> S34 BT.</p> <p>Corner falls on top of ascent, slopes S.</p> <p>Descend 14 ft. over SW. slope.</p> <p>40.25 Creek, 1 lk. wide, course S. <math>55^{\circ}</math> E.,; asc. 203 ft. over general E. slope.</p> <p>45.20 Leave dense brush, enter open pasture with scattering oak and patches of second-growth timber, edge bears NE. and SW.</p> <p>59.535 Point for the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap marked.</p> <div style="display: flex; justify-content: space-between; align-items: center;"> <div style="text-align: center;"> <math display="block">\begin{array}{r} \text{W } 1/16 \\ \hline \text{S } 27 \\ \text{S } 34 \\ 1962 \end{array}</math> </div> <div style="text-align: right;"> <p>FD BC - Scribbled 2 new trees D. Edwards 10/20/14 CS 65/86-31</p> </div> </div> <p>from which</p> <p>A fir, 39 ins. diam., bears N. <math>3\frac{1}{2}^{\circ}</math> E., 24 lks. dist., marked W 1/16 S27 BT.</p> <p>A fir, 20 ins. diam., bears S. <math>5^{\circ}</math> E., <math>19\frac{1}{2}</math> lks. dist. marked W 1/16 S34 BT.</p> <p>Ascend 24 ft. over E. slope.</p> <p>60.50 Ridge, bears N. <math>10^{\circ}</math> W., and S. <math>10^{\circ}</math> E.; desc. 276 ft. over SW. slope.</p> <p>69.20 Dirt road, 15 lks. wide, bears N. and S.</p> <p>79.38 The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, alder, maple, oak, madrone, dogwood, myrtle and chinquapin; undergrowth, vine maple, poison oak, hazel, arrowwood, huckleberry, salmonberry, blackberry and fern.</p>
	<p>From the cor. of secs. 32 and 33 only, on the S. bdy. of the Twp.</p> <p>N. <math>0^{\circ}</math> 24' E., bet. secs. 32 and 33.</p> <p>Ascend 52 ft. over S. slope, through heavy timber and sense undergrowth.</p> <p>4.15 Ridge, in saddle, bears E. and W.; desc. 72 ft. over NW. slope.</p> <p>5.10 Wet ravine, drains N. <math>40^{\circ}</math> W.; asc. 46 ft. over SW. slope.</p> <p>10.25 Spur, slopes W.; desc. 68 ft. over NW. slope.</p> <p>12.35 Creek, 1 lk. wide, course N. <math>60^{\circ}</math> W.; asc. 238 ft. over SW. slope.</p> <p>29.45 Top of ascent, slopes W.; desc. 110 ft. over NW. slope.</p> <p>35.40 Spur, slopes N. <math>30^{\circ}</math> W.; desc. 157 ft. over NE. slope.</p> <p>40.14 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 32 and 33 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap marked.</p>