

Dependent Resurvey of a Portion of the W. Bdy., T. 24 S., R. 6 W.

CHAINS

from which

A fir, 10 ins. diam., bears N. 45° E., 83 lks. dist.,
mkd. T24S R6W S19 BT.

A fir, 6 ins. diam., bears S. 55° E., 94 lks. dist.,
mkd. T24S R6W S30 BT.

From this point the $\frac{1}{4}$ sec. cor. of sec. 30 only, bears S. 0° 10' W.,
40.11 chs. dist., which has been perpetuated with a Douglas County
survey mark, an iron post, 1 $\frac{1}{2}$ ins. diam., firmly set, with brass
cap mkd.

COUNTY SURVEYOR'S OFFICE

WEST
S 25 | $\frac{1}{4}$ S 30
R 7 W | R 6 W
T 24 S
1959

from which the remains of the original bearing trees

A down fir, 24 ins. diam., bears S. 13° E., 61 lks.
dist., with a burned face.

A fir snag, 38 ins. diam., bears N. 66° W., 18 lks. dist.,
mkd. $\frac{1}{4}$ S BT.

and trees marked by the County Surveyor

A madrone, 32 ins. diam., bears S. 50° E., 66 lks. dist.,
mkd. W $\frac{1}{4}$ S30 CS BT.

A cedar, 6 ins. diam., bears S. 16° E., 108 lks. dist.,
mkd. W $\frac{1}{4}$ S30 CS BT.

and new bearing trees

A madrone, 17 ins. diam., bears N. 85° E., 146 lks. dist.,
mkd. $\frac{1}{4}$ S30 BT.

A fir, 6 ins. diam., bears S. 64° E., 128 $\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S30 BT.

I mark USBLM on the brass cap.

N. 0° 17' W., along the west boundary of sec. 19, marking and
blazing the true line.

Descend 40 ft. over N. slope, across logged area.

1.01 Point for the closing cor. of secs. 24 and 25, T. 24 S., R. 7 W.,
at proportionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 28 ins. in the ground,
with brass cap mkd.

T 24 S
R 7 W | R 6 W
CCS 24 | S 19
S 25
1962

FD OK Done
M121-64
APR. 1994
FD OK - Bentley
M123-6 10/95

from which

A fir, 38 ins. diam., bears S. 71° W., 172 lks. dist.,
mkd. T24S R7W S25 CC BT.