

Dependent Resurvey of a Portion of the W. Bdy., T. 24 S., R. 6 W.

CHAINS  
20.145

Point for the N 1/16 sec. cor. of sec. 19 only.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16  
S 19  
1962

from which

A fir, 18 ins. diam., bears N. 8½° E., 135 lks. dist., mkd. N 1/16 S19 BT.

A fir, 21 ins. diam., bears S. 42° E., 106 lks. dist., mkd. N 1/16 S19 BT.

Descend 280 ft. over steep N. slope.

27.50 Little Canyon Creek, 10 lks. wide, course S. 80° W.; asc. 5 ft. over S. slope.

28.75 Road, hard-surface, 50 lks. wide, on curve, bears S. 85° E. and S. 85° W.; asc. 465 ft. over steep S. slope.

40.29 The cor. of secs. 13, 18, 19 and 24, perpetuated with a Douglas County survey mark, an iron post, 1p ins. diam., firmly set, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

R	S 13	S 18	R
7	S 24	S 19	6
W	T 24	S	W
1959			

*FD. OK 12-92  
R. DOLAN M116-38  
FD OK 4-94  
R. DOLAN M121-64  
FD OK 10-95  
Benny M123-6*

from which the remaining original bearing trees

A fir, dead and down, 34 ins. diam., bears S. 66° E., 236 lks. dist., mkd. R on a chopped and burned face. This tree marked by Wm. R. Whipple, in 1891.)

A shell of an oak stump bears N. 40° W., 37 lks. dist., (Elder and Gile bearing tree)

and trees marked by the County Surveyor

A white oak, 7 ins. diam., bears N. 81° E., 95 lks. dist., mkd. S18 T24S R6W CS BT.

A fir, 7 ins. diam., bears S. 11½° E., 59 lks. dist., mkd. S19 T24S R6W CS BT.

A white oak, 5 ins. diam., bears S. 69° W., 42½ lks. dist., mkd. S24 T24S R7W CS BT.

A white oak, 7 ins. diam., bears N. 42° W., 69 lks. dist., mks. S13 T24S R7W CS BT.

and new bearing trees

A fir, 12 ins. diam., bears N. 73° E., 189 lks. dist., mkd. T24S R6W S18 BT.

A white oak, 6 ins. diam., bears S. 77° E., 48½ lks. dist., mkd. T24S R6W S19 BT.

A fir, 6 ins. diam., bears S. 9° W., 129 lks. dist., mkd. T24S R7W S24 BT.