

County Surveyor's Record, Douglas County, Oregon

-6-

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 6 W.

CHAINS	
0.50	Gully, drains S.; asc. 10 ft. over E. slope.
1.25	Spur, slopes S.; desc. 250 ft. over SW. slope.
8.15	Transmission Line, 2 strand, bears N. 60° W. and S. 60° E.
17.65	Road, hard-surfaced, 50 lks. wide, bears N. 60° W. and S. 60° E.
19.91	Point for the E 1/16 sec. cor. of sec. 19 and 30. Set an iron post, 30 ins. long, 2½ ins. diam., the top 10 ins. below the surface of an open field, with brass cap mkd. $\begin{array}{r} \text{E } 1/16 \quad \underline{\text{S } 19} \\ \quad \quad \quad \text{S } 30 \\ \quad \quad \quad 1962 \end{array}$ from which A fir, 6 ins. diam., bears N. 26° E., 13 lks. dist., mkd. E 1/16 S19 BT. A white oak, 10 ins. diam., bears S. 65° W., 175 lks. dist., mkd. S 1/16 S30 BT. Descend 50 ft. over SW. slope.
25.90	Creek, 5 lks. wide, course N. 55° W.; asc. 185 ft. over E. slope.
33.25	Spur ride, bears N. and S.; desc. 150 ft. over W. slope.
39.60	Little Canyon Creek, 10 lks. wide, course N. 30° W., curving W.
39.82	The ¼ sec. cor. of secs. 19 and 30, monumented by a maple, 16 ins. diam., with chopped and exposed faces on the N. and S. sides. This position is harmoniously related to existing original corners, has long been recognized as the corner by adjacent land owners, and is accepted as the best existing evidence of the original corner tree: from which a new bearing tree and reference monument An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, and in a mound of stone, 5 ft. base to top, for a reference monument bears NORTH ¼ lks. dist., with brass cap mkd. ¼ S19 RM 1962, and an arrow pointing to the true corner. A fir, 9 ins. diam., bears S. 73° W., 128 lks. dist., mkd. ¼ S30 BT. <hr/> N. 89° 52' W., beginning new measurement. Ascend 530 ft. over E. slope changing to SE. slope.
0.50	Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
13.85	Top of ascent, bench, asc. 230 ft. over NE. slope.
20.17	Point for the W 1/16 sec. cor. of secs. 19 and 30. Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{r} \text{W } 1/16 \quad \underline{\text{S } 19} \\ \quad \quad \quad \text{S } 30 \\ \quad \quad \quad 1962 \end{array}$ from which A fir, 12 ins. diam., bears N. 28½° E., 44 lks. dist., mkd. W 1/16 S19 BT.