

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 6 W.

CHAINS	
	<p>A fir, 10 ins. diam., bears S. 84° E., 101 lks. dist., mkd. W 1/16 S30 BT.</p> <p>Ascend 25 ft. over NE. slope.</p>
21.00	Spur, slopes N.; asc. 15 ft. over N. slope.
22.75	Head of ravine, drains N. 50° E.; asc. 50 ft. over NE. slope.
24.90	Ridge, bears N. and S.; desc. 105 ft. over W. slope.
31.35	Gully, drains N. 30° W.; asc. 10 ft. over NE. slope.
32.25	Spur, slopes N.; desc. 30 ft. over W. slope.
34.20	Dirt road, 15 lks. wide, bears S. 40° E. and N. 40° W.; asc. 90 ft. over NE. slope.
39.20	Spur, slopes N. 25° E.; desc. 35 ft. along N. slope.
41.94	<p>The cor. of secs. 19 and 30, only, on the W. bdy. of the Tp.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, and cedar; undergrowth, vine maple, salal, alder, ceanothus, blackberry and poison oak.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 11' E., bet. secs. 19 and 20.</p> <p>Ascend 75 ft. over SW. slope, through scattering timber and light undergrowth.</p>
5.50	Gully, drains S. 10° W.; asc. 100 ft. over SE. slope.
8.00	Spur, slopes S. 60° W.; asc. 25 ft. along W. slope.
11.75	Head of ravine, drains S. 35° W.; asc. 165 ft. over steep SW. slope.
16.25	Ridge, bears N. 75° W. and S. 75° E.; desc. 80 ft. over N. slope.
19.99	Wire fence bears E. and W.
20.21	<p>Point for the S 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 19/S 20 1962</p> <p>from which</p> <p>A fir, 18 ins. diam., bears N. 73½° E., 79 lks. dist., mkd. S 1/16 S20 BT.</p> <p>A fir, 13 ins. diam., bears S. 85° W., 159 lks. dist., mkd. S 1/16 S19 BT.</p> <p>Descend 425 ft. over NE. slope, changing to N. slope.</p>
40.15	Wire fence, bears N. 73° W. and S. 73° E.; desc. 15 ft. over N. slope.