

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 6 W.

CHAINS

40.42

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, perpetuated by a Douglas County survey mark, an iron post,  $1\frac{1}{2}$  ins. diam., firmly set 20 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

$\frac{1}{4}$  S | S  
 19 | 20  
 T 24 S R 6 W  
 1959

from which the remains of the original bearing trees

A cedar, 31 ins. diam., bears S.  $53^\circ$  E., 79 lks. dist., mkd.  $\frac{1}{4}$  S.

A sawed fir stump, 44 ins. diam., bears N.  $84\frac{1}{2}^\circ$  W., 59 lks. dist., mkd. S.

and a tree marked by the County Surveyor

A fir, 44 ins. diam., bears N.  $81\frac{1}{2}^\circ$  E., 68 lks. dist., mkd.  $\frac{1}{4}$  S20 CS BT.

and a new bearing trees

A cedar, 30 ins. diam., bears N.  $55\frac{1}{2}^\circ$  E., 113 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

A hemlock, 29 ins. diam., bears N.  $42^\circ$  W., 177 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

I mark BLM on the brass cap.

---

N.  $0^\circ$  21' E., beginning new measurement.

Descend 90 ft. over N. slope.

0.13 Dirt Road, 20 lks. wide, bears S.  $60^\circ$  E. and N.  $60^\circ$  W.

2.70 Creek, 6 lks. wide, course S.  $85^\circ$  W.; asc. 630 ft. over steep S. slope.

23.50 Broad spur, slopes S.  $75^\circ$  W.; desc. 30 ft. along broken W. slope.

40.03 The cor. of secs. 17, 18, 19 and 20, which is monumented with a sandstone, 14 x 10 x 5 ins., firmly set 8 ins. in the ground, marked "F" on the W. face; perpetuated by a Douglas County survey mark, an iron post,  $1\frac{1}{2}$  ins. diam., firmly set 24 ins. in the ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

S 18 | S 17  
 S 19 | S 20  
 T 24 S R 6 W  
 1959

from which the remains of the original bearing trees

A fir snag, 36 ins. diam., bears N.  $79^\circ$  E., 77 lks. dist., mkd. T24S S17

A burned madrone stump, bears S.  $21^\circ$  E., 65 lks. dist.

A fir snag, 40 ins. diam., bears S.  $69^\circ$  W., 135 lks. dist., mkd. S19 T24S