

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 6 W.

CHAINS	<p>A black oak, 8 ins. diam., bears S. 38° E., 115 lks. dist., mkd. <math>\frac{1}{4}</math> S19 CS BT</p> <p>and new bearing trees</p> <p>A black oak, 8 ins. diam., bears S. 29° W., 78 lks. dist., mkd. <math>\frac{1}{4}</math> S19 BT.</p> <p>A maple, 12 ins. diam., bears N. 6<math>\frac{1}{2}</math>° W., 97 lks. dist., mkd. <math>\frac{1}{4}</math> S18 BT.</p> <p>From this point an iron pin, <math>\frac{3}{4}</math> in. diam., firmly set flush with the ground, bears S. 21° E., 83 lks. dist.</p> <hr/> <p>West, beginning new measurement.</p> <p>Descend 415 ft. over W. slope.</p> <p>17.00 Creek, 3 lks. wide, course S. 40° W.; asc. 20 ft. over SE. slope.</p> <p>17.90 Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.</p> <p>18.55 Spur, slopes S. 30° W.; desc. 15 ft. over NW. slope.</p> <p>19.86 Point for the Witness Cor. to the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 8 ins. in the ground, to solid rock, supported in a mound of stone, 6 ft., base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>W 1/16 <math>\frac{S 18}{S 19}</math></p> <p>1962</p> </div> <p>from which</p> <p>A fir, 20 ins. diam., bears N. 15° E., 59 lks. dist., mkd. XBT</p> <p>A fir, 25 ins. diam., bears S. 72° W., 17 lks. dist., mkd. XBT</p> <p>Descend 10 ft. over NW. slope.</p> <p>20.06 True point for the W 1/16 sec. cor. of secs. 18 and 19 falls on the face of a bluff, 15 ft. high, extending N. 20° E. and S. 20° W., where it is impracticable to establish a permanent monumt.</p> <p>Descend 140 ft. over steep NW. slope.</p> <p>22.80 Creek, 3 lks. wide, course S. 45° W.; asc. 70 ft. over SE. slope.</p> <p>25.40 Transmission line, 2 strand, bears S. 25° E. and N. 25° W.; spur, slopes S.; desc. 70 ft. over SW. slope.</p> <p>33.80 Creek, 2 lks. wide, course S.; asc. 225 ft. over E. slope.</p> <p>40.25 Spur, slopes S. 45° E.; asc. 5 ft. along S. slope.</p> <p>42.12 The cor. of secs. 13, 18, 19 and 24, on the W. bdy of the Twp.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock and cedar; undergrowth, ceanothus, salal, maple, fir reproduction and poison oak.</p>
--------	--