

Subdivision of Section 19, T. 24 S., R. 6 W.

CHAINS

The following subdivision of section 19 was executed in conformity with legal surveying practice. The record of true line notes only is set forth in the following field notes.

From the $\frac{1}{4}$ Sec. cor. of secs. 19 and 30.

N. $0^{\circ} 14'$ E., on the N. and S. center line of sec. 19, marking and blazing the true line.

Descend slightly over small sand bar.

0.20 Little Canyon Creek, 10 lks. wide, course N. 70° W.; over small sand bar.

0.40 Same creek, 10 lks. wide, course N. 30° E.; asc. 200 ft. over SE. slope.

0.75 Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.

12.40 Spur, slopes E.; asc. 5 ft. along E. slope.

12.50 Dirt road, bears S. 15° E. and N. 15° W.

20.14 Point for the center S $1/16$ sec. cor. of sec. 19.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.

C
S $1/16$ | S 19
C
1962

from which

A cedar, 9 ins. diam., bears S. $7\frac{1}{2}^{\circ}$ E., 40 lks. dist., mkd. CS $1/16$ S19 BT.

A cedar, 10 ins. diam., bears S. 51° W., 10 lks. dist., mkd. CS $1/16$ S19 BT.

Descend 25 ft. along E. slope.

24.80 Spur, slopes NE. desc. 240 ft. over N. slope, changing to NE. slope.

34.55 Road, hard-surfaced, 50 lks. wide, bears S. 40° E. and N. 40° W.

35.35 Transmission line, 2 strand, bears N. 45° W. and S. 45° E.

35.45 Little Canyon Creek, 20 lks. wide, course N. 65° W.; asc. 10 ft. over SW. slope.

35.75 Enter cultivated land, edge bears N. 65° W. and S. 65° E.

40.28 Point for the center $\frac{1}{4}$ Sec. cor. of sec. 19, at intersection with the E. and W. center line.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.

C $\frac{1}{4}$
S 19
1962

from which

A fir, 12 ins. diam., bears N. 16° E., 243 lks. dist., mkd. C $\frac{1}{4}$ S19 BT.

A maple, 17 ins. diam., bears S. 55° E., 74 lks. dist., mkd. C $\frac{1}{4}$ S19 BT.