

Subdivision of Section 19, T. 24 S., R. 6 W.

CHAINS	
	The corner falls in a fence row which bears N. 40° E. and S. 40° W. Ascend 260 ft. over SW. slope.
48.00	Spur, slopes SE.; asc. 75 ft. along E. slope.
53.50	Spur ridge, bears N. 30° E., and S. 30° W., asc. 160 ft. over S. slope.
60.00	Base of bluff, 55 ft. high, faces SW.
60.44	Point for the center N 1/16 sec. cor. of sec. 19.  Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 5 ft., base to top, with brass cap mkd.
	$\begin{array}{c} C \\ N\ 1/16\   S\ 19 \\ C \\ 1962 \end{array}$
	from which  A face of a sandstone bluff, 6 ft. high, bears S. 84° E., 24 lks. dist., mkd. BXO  A face of a sandstone bluff 25 ft. high, bears N. 77° W., 90 lks. dist., mkd. BXO  Ascend 140 ft. over S. slope.
70.80	Broad spur, slopes S. 50° W.; desc. 15 ft. along W. slope.
80.60	The ¼ sec. cor. of secs. 18 and 19.  Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, and cedar; undergrowth, vine maple, arrowwood, myrtle, Oregon grape, poison oak, fir reproduction and ceanothus.
	From the ¼ sec. cor. of secs. 19 and 20.  N. 89° 56' W., along the E. and W. center line of sec. 19.  Ascend 15 ft. over NE. slope.
0.65	Spur, slopes N.; desc. 65 ft. over NW. slope.
1.10	The corner of a wire fence, extending S. 75° E. and 75° W.
6.80	Creek, 1 lk. wide, course N. 20° W.; asc. 50 ft. over E. slope.
8.85	Spur, slopes N.; desc. 55 ft. over W. slope.
12.65	Creek, 1 lk. wide, course N. 15° W.; asc. 10 ft. over E. slope.
15.00	Spur, slopes N.; desc. 5 ft. over NW. slope.
19.92	Point for the center E 1/16 sec. cor. of sec. 19.  Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C \\ E\ 1/16 \\ S\ 19 \\ C \\ 1962 \end{array}$
	from which