

Subdivision of Section 19, T. 24 S., R. 6 W.

CHAINS	
	A fir, 18 ins. diam., bears N. 70° E., 173 lks. dist., mkd. CE 1/16 S19 BT.
	A cedar, 18 ins. diam., bears S. 18° W., 63 lks. dist., mkd. CE 1/16 S19 BT.
	The corner falls on the S. edge of a dirt road, bears N. 75° E. and N. 75° W.
	Ascend 10 ft. over E. slope.
21.40	Spur, slopes N. 25° W.; desc. 185 ft. over NW. slope.
21.90	Road, dirt, on curve, 35 lks. wide, from S. 65° E. curving to S. 45° W.
23.00	Road, dirt, 15 lks. wide, bears N. 30° E. and S. 30° W.
32.85	Creek, 5 lks. wide, course S. 60° W.; asc. 15 ft. over creek bottom
35.30	Creek, 2 lks. wide, course S. 10° W.; asc. 20 ft. over E. slope.
37.75	Spur, slopes S.; desc. 35 ft. over SW. slope.
39.84	The center $\frac{1}{4}$ sec. cor. of sec. 19.
	Thence over level land.
42.55	Little Canyon Creek, 20 lks. wide, course N. 15° W.; asc. 70 ft. over NE. slope.
43.70	Transmission line, 2 strand, bears N. 32° W. and S. 32° E.
47.10	Road, hard-surfaced, 50 lks., wide, bears N. 40° W. and S. 45° E.
52.00	Spur, slopes N. 15° E.; desc. 10 ft. over NW. slope.
55.20	Creek, 1 lk. wide, course N. 40° E.; asc. 110 ft. over SE. slope.
59.75	Spur, slopes N. 40° E.; asc. 5 ft. along N. slope.
60.06	Point for the center W 1/16 sec. cor. of sec. 19.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.
	C $\frac{W 1/16}{S 19}$ C 1962
	from which
	A fir, 8 ins. diam., bears N. 49° E., 52 lks. dist., mkd. CW 1/16 S19 BT.
	A fir, 21 ins. diam., bears N. 54° W., 31 lks. dist., mkd. CW 1/16 S19 BT.
	Ascend 350 ft. over steep N. slope, changing to NE. slope.
69.80	Ridge, bears N. 40° W. and S. 35° E.; desc. 280 ft. over W. slope, changing to NW. slope.
76.00	Ravine, drains S. 75° W.; asc. 55 ft. along S. slope, changing to SW. slope.
82.09	The $\frac{1}{4}$ sec. cor. of sec. 19 only on the W. bdy. of the Twp.