

County Surveyor's Record, Douglas County, Oregon

-15-

Subdivision of Section 19, T. 24 S., R. 6 W.

CHAINS	
34.90	Little Canyon Creek, 10 lks. wide, course N. 10° W.; asc. 250 ft. over steep E. slope.
39.79	The center S 1/16 sec. cor. of sec. 19.
<p>From the W 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 09' E., along the N. and S. center line of the SW$\frac{1}{4}$ of Sec. 19.</p> <p>Descend 60 ft. over NE. slope.</p>	
2.50	Ravine, drains E.; asc. 10 ft. over SE. slope.
3.90	Spur, slopes E.; desc. 205 ft. over NE. slope, changing to E. slope.
14.25	Dirt road, 20 lks. wide, bears S. 40° E. and N. 40° W.
20.16	Point for the SW 1/16 sec. cor. of sec. 19, at the intersection with the E. and W. center line of the SW $\frac{1}{4}$.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.
	SW 1/16 S 19 1962
	from which
	A fir, 10 ins. diam., bears S. 60° E., 15 lks. dist., mkd. SW 1/16 S19 BT.
	A chinquapin, 8 ins. diam., bears S. 36 $\frac{1}{2}$ ° W., 66 lks. dist., mkd. SW 1/16 S19 BT.
	Descend 5 ft. along E. slope.
20.25	Spur, slopes N. 60° E.; desc. 370 ft. over NW. slope.
34.40	Creek, 2 lks. wide, course N. 20° E.; asc. 55 ft. over SE. slope.
40.20	Spur, slopes N. 40° E.; desc. 5 ft. over N. slope.
40.33	The center W 1/16 sec. cor. of sec. 19.
<p>From the center S 1/16 sec. cor. of sec. 19.</p> <p>N. 89° 56' W., along the E. and W. center line of the SW$\frac{1}{4}$.</p> <p>Ascend 75 ft. over E. slope.</p>	
3.15	Spur, slopes N.; dirt road on curve, 20 lks. wide, bears S. 45° E. and S. 45° W.; desc. 65 ft. over NW. slope.
13.30	Creek, 1 lk. wide, course N. 20° E.; asc. 230 ft. over steep E. slope.
19.75	Spur, slopes N. 60° E.; desc. 5 ft. over NW. slope.
20.21	The SW 1/16 sec. cor. of sec. 19.
	Descend 25 ft. over NW. slope.
21.00	Head of ravine, drains N. 20° W.; asc. 55 ft. over NE. slope.